manual

gb5

The new GB5 is designed with traditional European style and is for those locations with an eye on classic aesthetics but that still demand the highest performance. This new machine combines the most advanced La Marzocco proprietary electronics with the industry-leading temperature stability and hydraulic systems that always ensure maximum consistency.






Operating Manual V1.0 - 10/2020 MAN 25 1

1. General Warnings and Safety Specifications

Chapters





La Marzocco S.r.l.

page 3	Via La Torre 14/H
page 8	Località La Torre 50038 Scarperia e San Piero (Firenze) - ITALIA
page 11	(
	www.lamarzocco.com
page 17	info@lamarzocco.com
200	T: +39 055 849 191
page 20	F: +39 055 849 1990
page 21	Original instructions verified by the
page 23	manufacturer. 回過影路回
page 24	
	宣影容納
page 25	Scan QR Code to view the complete

certifications available:







Printed on recycled paper.

the techcenter website.

page 28

Software Programming Guide available on

1. General Warnings and Safety Specifications

▲ WARNING

This machine is for professional use only and should be installed in locations where its use and maintenance is restriced to trained personnel. Children are forbidden to operate or play with the machine.

▲ WARNING

The Coffee machine must be placed in a horizontal position on a counter higher than 80 cm from the ground.

<u> Warning</u>

This machine is not suitable for outdoor use. Jets of water should not be used to clean the machine, nor should it be placed where water jets are used.

CAUTION

As already mentioned in the preceding notes, the manufacturer shall not be held responsible for damage to objects, animals and/or people whenever the machine has not been installed according to the instructions contained in this manual, and is not used to do what it was designed for (i.e. preparing coffee and hot drinks).

1) Important safeguards

- The weighted sound pressure level of the machine is lower than 70dBA.
- Use, cleaning and maintenance of this coffee machine are realized by people (including children more than 8

years of age) with reduced physical, sensory or mental capabilities, or lack of experience and knowledge, as long as they have been given supervision or instructions concerning the use of the appliance by a person responsible for their safety and if they understand dangers.

- Children should be supervised to ensure that they do not play with the appliance.
- Keep the appliance and its cord out of the reach of children less than 8 years of age.
- 2) This operating manual is an integral and essential part of the product and

must be supplied to users. Users are asked to read the enclosed warnings and cautions carefully, as they provide valuable information safetv concerning during installation, operation and This manual maintenance. must be kept in a safe place and be available for consultation to new and experienced users alike.

- 3) Ensure product's integrity by inspecting the packaging, making sure it presents no signs of damage which might have affected the enclosed machine.
- **4)** Check the machine's integrity after having carefully removed the packaging.

Note: In case of doubt, do not go

on any further and contact your dealer or retailer immediately. They will send out specialized personnel authorized to perform service on the espresso machine.

- 5) Packaging (boxes, plastic bags, foam parts and whatever else) must not be left around within easy reach of children, due to the potential danger it represents, nor be discarded in the environment.
- **6)** Check to see that data on the rating plate corresponds to those of the main electrical supply which the machine will be hooked up to.
- 7) The equipment must be installed to comply with the applicable federal, state or local electrical and plumbing codes. The installation

also must comply to the manufacturer's instructions, and must be performed by qualified and authorized personnel.

- 8) Incorrect installation may cause for injury/damages to people, animals or objects, for which the manufacturer shall not be held responsible.
- 9) Safe electrical operation of this device will be achieved only when the connection to the power outlet has been completed correctly and in observance of all local, national, and international electrical codes and safety regulations, and particularly by grounding the unit. Make sure grounding has done properly as it been

represents a fundamental safety requirement. Ensure qualified personnel check such connection.

- **10)** Furthermore, you must ensure that the capacity of the available electrical system is suitable for the maximum power consumption indicated on the espresso machine.
- 11) We do not recommend adapters, using multiple plugs and/or extension cords. If you cannot avoid using them, make sure that they are exclusively of the kind which conforms to local, national, and international electrical codes and safety regulations, being careful not to exceed the power and current ratings indicated on such adapters

and extension cords.

- 12) This device must be used exclusively for the functions it has been designed and built for. Any other application is inappropriate and dangerous. The manufacturer shall not be held responsible for any damages caused by improper and/or irrational use.
- This machine should not be installed in kitchens.
- 13) Using any electrical device requires that certain fundamental rules he observed. In particular:
- do not touch the device with wet or humid hands and feet:
- do not use the device while having no shoes on your feet:
- do not use extension cords

- in bath or shower rooms:
- do not unplug the device from the power outlet by pulling on the power supply cable:
- do not expose the device to atmospheric agents (rain, sun, etc.):
- do not allow children or untrained people to use this device:
- do not clean the control panel with a wet cloth since it is not watertight.
- 14) Before carrying out any maintenance and/or cleaning operations, turn the main switch, which is located on the front left of the machine. to the "O" or "OFF" position, and disconnect the machine from the electrical network by unplugging the cord or

by switching off the relative circuit breaker. For any cleaning operation, follow exclusively the instructions contained in this manual.

15) In case the machine is operating in a faulty manner or breaks down, disconnect it from the electrical network (as described in the preceding point) and close the water supply valve. Do not attempt to repair it. Contact a qualified and authorized professional to perform any repair. Any repairs must be performed exclusively by the manufacturer or by an authorized centre using only original parts. Non compliance with the above could compromise the safe operation of the machine.

- **16)** You should plan to make use of an omnipolar connector during installation, as required by local, national, and international electrical codes and regulations.
- 17) In order to avoid dangerous overheating problems, it is recommended that the power supply cable be fully unfurled.
- **18)** Do not obstruct air intake and exhaust grilles and, in particular, do not cover the cup warmer tray with cloths or other items.
- 19) The machine's power supply cable must not be replaced by users. In case the power supply cable becomes damaged, shut off the machine and disconnect the machine from the electorical

- network by switching off the relative circuit breaker and close off the water supply; to replace the power supply cord, contact qualified professionals exclusively.
- **20)** These instructions are also available in an alternative format on a website http://techcenter.lamarzocco.com.
- 21) The machine should be placed on a flat counter and must be placed in settings with the following temperatures:

Minimum room temperature: 5°C/41°F;

Maximum room temperature: 32°C/89°F.

22) Check the package to make sure that the following

accessories are included:

- a number of 1-dose and 2-dose portafilters orresponding to the number of groups;
- replacement 1-dose and 2-dose filters (one of each);
- 1 tamper;
- 1 blind filter;
- cleaning detergent, for the groups;
- 3 stainless steel braided hoses for water connections;
- 1,5 mt of reinforced plastic tubing for drainage;
- 1 hose clamp.
- 23) If the machine has been temporarily housed in settings with a room temperature of less 0°C/32°F, the machine must be placed in a warmer environment in order to gradually defrost the


hydraulic system prior to use.

24) Water pressure supply must be between 0,4 and 0,8 MPa.

The maximum inlet water pressure shall be at least 1,0 MPa (Denmark, Norway, Sweden).

- 25) The machine is intended to be permanently connected to fixed wiring, and it is mandatory that a residual current device (RCD) with a rated residual operating current not exceeding 30mA is installed.
- **26)** This machine is designed only for preparing coffee and hot drinks.
- **27)** Any modification to the equipment is prohibited; the manufacturer cannot

be held liable for damage to property, animals, and/ or persons if the equipment undergoes technical and aesthetic changes, changes in performance and characteristics, and in general is tampered with in one or more of its constituent components.



GB5	2 groups	3 groups	4 groups
A [mm]	770	970	1210
B [mm]	640	640	640
C [mm]	470	470	470
WEIGHT [kg]	68	78	90

2. Definition of Available Models

This operating manual refers exclusively to the following models, of our own manufacture:

GB5, model AV & EE, ABR 2, 3 and 4 groups




Fig. 1 - Model AV & EE, ABR with 2, 3 or 4 groups

Legend

- 1 Main Switch
- 2 Pressure Gauge (steam boiler)
- 3 Pressure Gauge (coffee boiler)
- 4 Brew Groups
- 5 Control Panel
- 6 Group #1 Keypad
- 7 Digital Display
- 8 Steam Wand
- 9 Steam Knob
- 10 Hot Water Wand
- 11 Removable Drain Tray
- 12 Hot Water Mix Valve
- 13 Precision Scale
- 14 Manual Brew Switch (EE model)
- 15 Hot Water Switch (EE model)

For additional information on electronics, keypads, and software programming, please see the section entitled Software Programming your Espresso Machine.

1) General Description

The machine is built in 2, 3 and 4 coffee group versions and is essentially composed of the following parts:

- Steam Boiler (produces steam and hot water):
- Coffee ("saturated") boiler:
- Brewing groups;
- Exterior Cover;
- Water pump.

2) Description of the various parts

Steam Boiler

The Steam Boiler consists of a cylindrical tank, of varying length according to the number of coffee groups, which is made of AISI 300 series stainless steel. Each unit is subjected to a hydraulic test, at a pressure of 6 bar, and has an operating pressure of 1.3-1.5 bar. The following is a list of effective volumes and power ratings according to the number of groups installed:

2 groups 7 liters 3000 Watts 3 groups 11 liters 4000 Watts 4 groups 15 liters 4350 Watts

Covers are welded at either end of the cylindrical tank and on one of them there is a housing for the water heating element, which allows the steam boiler to reach operating pressure within approximately 25

minutes. Operating pressure is maintained by temperature probe and PID controller. The steam boiler has various fittings used for safety devices, for supplying hot water and steam, and for the heating element.

Composed of AISI 300 series stainless steel tube. Heating is accomplished through an immersion-type plated heating element.

- Operating pressure of 1.3-1.5 bar, controlled automatically through a pressure switch or a temperature probe, adjusted to open the heating element supply circuit at 1.5 bar and close it at 1.3 bar.
- The pressure is displayed by means of a pressure gauge with a scale of 0 to 2 bar.
- Safety device, based on an expansion type mechanical valve, with counteracting spring adjusted to 1.8 bar.
- Testing: hydraulic test at 4.5 bar performed on ready-to-use small boilers, at our factory.

• Coffee Boiler

The Coffee Boiler consists of a cylindrical tank made of AISI 300 series stainless steel. One each group (hot water generator for brewing coffee).

Each unit is subject to a hydraulic test, at a pressure of 18 bar, and has an

operating pressure of 9 bar. The following is a list of effective volume and power ratings according to the number of groups installed:

GR5 X-

2 groups	2 x 1,3 liters	2 x 800 Watt
3 groups	3 x 1,3 liters	3 x 800 Watt
4 groups	2 x 3,4 liters	2 x 1400 Wat

GB5 S:

2 groups	1 x 3,4 liters	1 x 1400 Watt
3 groups	1 x 5,0 liters	1 x 1900 Watt
4 groups	2 x 3,4 liters	2 x 1400 Watt

Covers are installed at either end of the cylindrical tank and on one of them there is housing for the water heating elements. The temperature of the coffee boiler is maintained by an electronic temperature controller (PID capable) with an accuracy of 0.2°C. The brewing groups are installed on the boiler.

Composed of an AISI 300 series stainless steel tube. Heating is accomplished through an immersion-type plated heating element.

- Operating temperature 95°C (adjustable), controlled automatically by an electronic temperature controller with an accuracy of 0.2 °C. Operating pressure of 9 bar.
- Pressure is displayed through a pressure gauge with a scale from 0 to 18 bar.

- Safety device, based on an expansion type mechanical valve, with ounteracting spring adjusted to 13 bar.
- Testing: Hydraulic test at 18 bar performed on ready-to-use small boilers, at our factory.

Brewing groups


They consist of a precision casting made of stainless steel. The brewing group accepts the portafilter used to hold the ground coffee; the espresso flows through the brewing group, through the portafilter basket, through the portafilter spout, and into the cup(s) after the brewing button has been pressed.

Exterior cover

The exterior consists of painted and stainless sheet steel panels. To provide good aesthetics, to optimize ergonometrics for the operator and to reduce the chance of damage to a minimum.

• Water pump

The rotary vane pump, is installed on the water supply tubing and is set up to operate anytime the coffee groups are activated, and through an autofill system whenever the water boiler needs to be replenished.



• Machine CE plate:




• Machine ETL plate:



• Machine KC plate:



3. Installation



WARNING

The machine is intended to be permanently connected to fixed wiring, and it is mandatory that a residual current device (RCD) with a rated residual operating current not exceeding 30mA is installed.

WARNING

The Coffee Boiler and Steam
Boiler contain water at
elevated temperature. Water
temperature over 125°F /
52°C can cause severe burns
instantly or death from scalding
(Coffee Boiler 207°F/97°C Steam Boiler 256°F / 124°C)

WARNING

Replace fuses with the same size, type and rating. e.g. F1 = 2A, 250V

			(W)	(A)	WATTAGE	WATTAGE	WATTAGE	` ′
	2GR	AC220-240V/60H AC208-240/60H AC380/50Hz		23,7 xx 10,7	1400	3000	5445	SEE ELECTRICAL
GB5 S	3GR	AC220-240V/60H AC208-240/60H AC380/50Hz		31,5 xx 14,4	1900	4000	7238	CONNECTIONS FOR DETAILS
	4GR	AC220-240V/60H AC208-240/60H AC380/50Hz		38 xx 16	2800	4350 4350 5000	8763 8763 9467	FOR DETAILS
POWER CORD: 3 X WIRES 1 X BLUE (NEUTRAL) 220V 1 X BROWN (PHASE) 1 X YELLOW & GREEN (GROUND) 1 X YELLOW & GREEN (GROUND) 1 X YELLOW & GREEN (GROUND) 4 X WIRES 1 X BLACK (PHASE) 220V 4 X WIRES 1 X BLACK (PHASE) 1 X YELLOW & GREEN (GROUND) 4 RESPECT LASO THE LOEST HEE HOW TO CONNECT EACH WIRE TO THE PLUG. RESPECT LASO THE LOEST SAFETY RESULTATIONS.								
(ONLY FOR ETL) POWER CORD:								
ONLY FOR 2 GROUPS: NEMA 6-30P			ON	LY FOR 3 AND	4 GROUPS: N	EMA 6-50P		
35, 54, 15 25, 649, 15 25, 7880 25, 7880 25, 7880 25, 7880 25, 7880 25, 7880 25, 7880 25, 7880 26, 7880 27, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 28, 7880 2			88 042.0 W 640.3	42.022.0	35. 7 max	41.012.0		

INPUT

BOILER

TOTAL

WATTAGE

SIZE (mm²)

BOILER

WARNING

At each installation, the machine should be equipped with a new set of tubes for plumbing and related gaskets.

▲ WARNING

Water pressure supply must be between 0,4 and 0,8 MPa if sufficient pressure is not available we suggest that an additional water supply system is used.

▲ WARNING

Before making any electrical connections make sure that the two strain relief connectors are firmly secured to the body of the machine in order to prevent inadvertent stress on the power cables.

WARNING

This machine should not be installed in kitchens.

MODEL/SERIES

GROUP

V/Hz

POWER

▲ WARNING

Hazardous voltage disconnect from power supply before servicing.

► WARNING

The motor pump must be situated close to the machine in an accessible place for maintenance but not for accidental interference and where there is an optimal air circulation.

► WARNING

The manufacturer declines any responsibility for any event leading to liability suits whenever grounding has not been completed according to current local, national, and international regulations and electrical codes, or other electrical parts have been connected improperly.

WARNING

This appliance is not intended for use by persons (including children) with reduced physical, sensory or mental capabilities, or with lack of experience and knowledge, unless they have been given supervision or instruction concerning the use of the appliance by a person responsible for their safety.

WARNING

- U.S.A. and CANDA only - Do not connect to a circuit operating at more than 150V to ground on each leg.

▲ WARNING

This machine is not suitable for outdoor use. Jets of water should not be used to clean the machine, nor should it be placed where water jets are used.

WARNING

In order to prevent cracks or leakage: do not store or install the Coffee machine in places where in boiler or hydraulicsystem to freeze.

Note:

- The drinking water mains valve and the circuit breakers for the electrical system need to be located in the most convenient position for the operator to access them easily and quickly.
- This machine complies with the standard 61000-3-11, the impedance at the supply interface must be Zmax= 0.22 Ω.

1) Installation on the counter

The image below shows the recommended method to drill the hole on the counter.




Fig. 2 - Installation guide

2) Accessories

In order to proceed with installation, it is necessary that the following are available:

- Pipes carrying drinking water with a 3/8"G (BSP) end connection; (3/8" Compression for USA and Canada)
- Electrical Supply according to the specification of the espresso machine purchased:
- Single/Three phase 220VAC 50/60
 Hz electrical connection with ground,
 protected socket and approved
 interlock switch
- Single phase 200VAC 50/60 Hz electrical connection with ground, protected socket and approved interlock switch
- Three-phase, 380VAC 50 Hz electrical connection with neutral + ground, near the bench on which the machine is installed and terminating in a suitable protected fivepole socket equipped with an approved interlock switch
- Waste water drain system.

3) Water test kit

In order to enable you to check if your water supply is within the suggested ranges, La Marzocco machines will be equipped with two units of a quick water test kit (see image below) including 6 test-strips and instruction cards.



The parameters that you can measure are Total Hardness, Total Iron, Free Chlorine, Total Chlorine, pH & Total Alkalinity, Chlorides.

Ideally, you should perform a test on the water BEFORE the water treatment system and again AFTER the water system in order to verify if this is actually matching our suggested ranges.

Once the test has been performed, learn which treatment system is most appropriate for your particular water supply by filling out the online water calculator on our website: LA MARZOCCO WATER CALCULATOR (http://www.lamarzocco.com/water_calculator/).

4) Water supply connection

In order to connect the machine up to the water mains proceed according to the indications given in the chapter about Installation and in compliance with any local/national safety standards of the location in which the machine is being installed. The equipment is to be installed with adequate backflow protection to comply with applicable federal, state, and local codes.

To guarantee a correct and safe functioning of the machine and to maintain an adequate performance level and a high quality of the beverages being brewed it is important that the incoming water be of a hardness greater than 7°f (70ppm, $4^{\circ}d$) and less than $10^{\circ}f$ (100ppm, $6^{\circ}d$), pH should be between 6.5 and 8.5 and the quantity of chlorides be less than 30mg/l . Respecting these values allows the machine to operate at maximum efficiency. If these parameters are not present, a specific filtration device should be installed, while always adhering to the local national standards in place regarding potable water.

Then connect the inlet of the water filter/softener (if present) to the drinking water supply using one of the supplied stainless steel braided hoses. Before connecting the filter to the water pump, flush the water supply line and the filtration system in order to eliminate any residual particles which could otherwise get stuck in taps or valves thus preventing them from working

properly. Connect the water supply connection of the espresso machine to the water pump outlet using one of the supplied stainless steel braided hoses. Then connect the water pump inlet to the water filter/softener outlet (if present).

Note: The water pump is a differential pressure volumetric pump and has been designed to be used exclusively with cold water. Make sure that water is always present while the pump is operating, otherwise air can be introduced into the brew boiler causing an undesireable condition and the pump can be damaged.

5) Electrical connections

a) Power supply cord

- This is the main power supply cable that provides power to the entire espresso machine. There are different types of cable based upon the electrical requirements of the espresso machine purchased:
- 200/220VAC 1 Phase 3-core cable with 4/6/10mm2 cross section or AWG 12/10/8 for 2,3 4 group versions, secured to espresso machine via a strain relief connector
- 220VAC 3 Phase 4-core cable with 4 mm2 cross section for 2, 3 and 4 group versions, secured to espresso machine via a strain relief connector
- 380 VAC 3 Phase 5-core cable with 2.5mm2 cross section for 2, 3 and 4 group

versions, secured to espresso machine via a strain relief connector.

b) Water pump motor power cord


This is the power supply for the water pump motor. The internal electronics will switch the pump motor on when needed.

• 3-core cable with 1.5 mm2 cross section or 3-core AWG 16 (for UL version) secured to espresso machine via a strain relief connector.

c) Quick connection between the water pump and the espresso coffee machine

The electrical connection must be made through the use of the connectors, as shown in the following figures:

- View of the connectors;



- Cable connection;



- Cable tightening;



6) Waste water drain connection

The espresso machine drain is to be connected by means of the included reinforced plastic tubing. Connect one end of the reinforced plastic tubing to the drain hose connection on the left side of the espresso machine, secure with included hose clamp. Connect the other end to a suitable waste water collection system.

In case such a system is not available, drained liquids may be collected in a suitable bucket and any necessary drain pipe extensions shall be made using steel-lined PVC tubing and suitable hose clamps.

Water specifications table

		Min.	Max.
T.D.S.	ppm	90	150
Total Hardness	ppm	70	100
Total Iron (Fe ⁺² /Fe ⁺³)	ppm	0	0,02
Free Chlorine (Cl ₂)	ppm	0	0,05
Total Chlorine (Cl ₂)	ppm	0	0,1
рН	value	6,5	8,5
Alkalinity	ppm	40	80
Chloride (Cl ⁻)	ppm	not more	30

N.B.: Test water quality (the warranty is void if water parameters are not within the range specified in the section "installation")

4. Machine Operation and Coffee Preparation

CAUTION

Never remove the filter holder when water is being delivered. This operation can be extremely dangerous since the high pressure built-up inside the blind filter would spray out hot and slightly caustic water, which may cause severe burns. The Coffee Boiler contains water at elevated temperature. Water temperature over 125°F / 52°C can cause severe burns instantly or death from scalding.

WARNING

The machine must not be dipped in, nor splashed with, water in order to clean it. For cleaning operations, please follow the instructions listed below very carefully.

IMPORTANT

To improve the flavor of the espresso, the temperature of the water in the coffee boiler and therefore of the groups may eventually be raised or lowered via the digital display (please consult the Software Programming Manual for detailed instructions).

1) Starting the espresso machine

a) Filling the boilers with water


Once the installation procedures have been completed, it is necessary to fill the boiler tanks with water. Complete the following procedure to properly fill the boiler tanks:

• Coffee hoiler

The water flows inside the coffee boiler directly, as soon as the water system and water filter/softener taps (if present) are opened. Since the inflow of water will compress the air in the boiler it will be necessary to remove or "bleed" the air from the coffee boiler. All air must be removed in order to completely "saturate" the coffee boiler/group assemblies. To remove the air from the boiler, "bleed the groups", it will be necessary to remove the group cover from the top of the machine. First remove the cup tray grates from the top of the machine exposing the cup tray. Remove the screws securing the group cover and then remove

it. Once removed the top of the groups will be exposed.

Loosen the bleed screws one at a time (see picture) to allow air to escape until water flows from below the screw head.



Tighten the screw to stop the water from flowing. Over tightening can cause damage to the sealing washer and the group cover. Repeat this procedure for all groups. Once all air is removed from the coffee boiler, reinstall the group cover by following the removal instructions in reverse.

• Steam boiler

Turn the main switch (item 1 in Fig. 1) to position "1" or ON, the automatic steam boiler level gauge will be switched on, activating the auto-fill solenoid valve and the motor pump. This will fill the steam boiler to a predetermined level and will shut off when full.

Note: It may happen that the air inside the steam boiler builds up pressure (which may be detected through the pressure gauge - item 2, fig. 1) when the water is allowed to flow in; this "false" pressure must be eliminated by opening the steam valves (item 9, Fig. 1).

b) Turning the espresso machine on

Once you have completed these procedures, check the display. Press enter to confirm that the preceding procedures are complete.

The installation is now complete and the espresso machine should be heating to the operating temperatures.


2) Waiting for the espresso machine to heat to operating temperature

During this time, it may happen that the pointer of the coffee boiler pressure gauge reaches as high as 14-15 bar. This may happen anytime that the heating element is in the on condition. In this case it is necessary to adjust the expansion valve in such a way that the pressure may never exceed 11-12 bar. In normal operating conditions, the coffee boiler pressure gauge can read anywhere from 0-12 bar.

When brewing, the pressure should be set to 9 bar.

When the steam boiler reaches operating temperature, the light on the Tea dispense button will light.

When the espresso machine is ready to operate all lights on the keypads will light.



3) Brewing after first installation

Once the first installation procedures are finished, before proceeding with brewing coffee, hot water and steam, please follow these steps:

- Engage the portafilters by inserting them into each group, brew water through each group for at least two minutes.
- Being careful to avoid burns, turn on each steam wand for at least one minute.
- Turn on the hot water valve for the time necessary to allow the following quantities of water to be brewed:

At least 1 liter for a 1/2 group machine At least 2 liters for a 3 group machine At least 3 liters for a 4 group machine

4) Installing the portafilters

Install the portafilter(s) by inserting them into the group and rotate the handle from left to right. When the portafilters are inserted properly, you can press any of brew buttons to start the flow of water through

the portafilter. You should allow hot water to pass through the empty portafilter(s) for a few seconds each time, in order to pre-heat the portafilter.

Note: It is important to leave the portafilters installed in the espresso machine when not in use. The portafilter must remain heated for the brew process to function correctly.


5) Water pump

Whenever you are brewing coffee, and you can adjust the pump pressure by turning the by-pass screw (below the plug located on the side to which the pump power supply is connected) clockwise to increase and counter-clockwise to reduce pressure. Adjust pressure only when at least one group is brewing coffee.

Note: When the heating element in the coffee boiler is energized, the water will expand increasing the start-up pressure. Once the maximum pressure is reached, the expansion (safety) valve should start working by discharging a few drops of water, in order to prevent such pressure from exceeding 11-12 bar.

In case the pressure exceeds 12 bar, you must adjust the expansion valve by unscrewing the cap slightly. If this is not sufficient, remove the valve and clear away any calcium deposits. This remedy is valid

also in case the valve remains open in the drain position (i.e. the pressure cannot increase to 8 bar approx.).



6) Brewing coffee

It is now possible to remove one of the portafilters to make an espresso beverage. Place some ground coffee in the filter itself: 1 dose (approximately 6-7 g) for the small filter, 2 doses (2 approximately 12-15 g) for the larger filter. Press down on the ground coffee with the supplied tamper and install the filter holder up again to the bottom of the group and then press a button.

Note: Some baristas believe it is important to press the brewing button prior to installing the portafilter to allow the water to flush any remaining coffee oils and particles from the group. Some also flush just after brewing coffee for the same reason. Please experiment to find the best possible procedure for you.

7) Controlling the brew process using volumetric programming (AV model only)

This espresso machine allows the volumetric programming of each of the first two buttons on each group (numbered left to right). Please consult the Software Programming Manual for further instructions.

8) General notes for coffee preparation

The portafilters must remain heated since they are at the lowest position of the group itself, and they are partially isolated due to the rubber gasket between them. This can be accomplished by leaving the portafilters installed in the machine when not in use. The portafilters may also be actively heated. This procedure may be carried out by brewing some hot water through the portafilter then turning off the water flow, before making coffee.

We recommend removing the spent coffee puck directly after brewing.

The size of the coffee granules is extremely important in preparing a good cup of coffee, other than the type of coffee mix used, quite obviously. The ideal grinding can be determined by making various coffees using the amount of ground coffee that you would normally use for each cup (we recommend at least 6-7g). The best grinding is that which allows coffee to flow out from the filter holder spouts neither too slowly (drop by drop) nor too quickly

(quick light brown flow). A general rule is that a double dose should dispense approximately 25cc or 2 fluid oz. of espresso in approximately 25 seconds.

9) Cup Warmer

Press Cup Warmer Button for enabled or disabled the cup warmer. This function work in two modes continuous or timed (see the Software Programming Manual for further instructions).



Cup Warmer Button

5. Dispensing Steam and Hot Water

1) Steaming milk or other liquids

In order to allow for any condensed water in the wand to be released ALWAYS allow some steam to be discharged by turning on the valve before inserting the steam wand into the pitcher of liquid to be heated.

Dip one of the 2 steam wands (part 8, page 7) which are connected to the steam valve, into the liquid to be heated, turn the steam knob gradually until steam comes out at the end of the wand.

The steam will transfer heat to the liquid raising its temperature up to boiling point. Be careful not to allow liquid to overflow in order to avoid severe burns.

In order to prevent the heated liquid from being sucked back into the steam boiler it is recommended before using the wand that you purge the steam valve and steam wand by opening the valve for a few seconds to allow steam to escape to the atmosphere from the end of the steam wand. Failure to do so can cause the heated liquid to transfer from the heated liquid container to the steam boiler (via vacuum created from cooling parts). This condition is undesireable and can cause contamination in the steam boiler. After use remember to purge the wand by opening the steam valve for a few seconds, and then clean the outside of the wand

itself with an appropriate cloth.


In order to prepare milk for making cappuccino with the right amount of foam, go through the following steps:

• After purging the steam wand place the container half-full of milk underneath, carefully open the steam valve and raise the container so as to bring the wand end to a point just below the surface of the milk; at this point, move the container up and down just enough to dip the nozzle end in and out of the milk until you get the right amount of foam, bring the temperature of the milk almost up to 149/158°F or 65/70°C. You can then pour this milk into a cup containing warm espresso and you will end up with a fresh cup of cappuccino.

2) Preparing tea and other hot drinks.

You may dispense hot water by using the fixed nozzle (part 6, page 7). To dispense hot water, press the hot water button.

This button commands hot water delivery.



The temperature of the water may be adjusted by adjusting the mixing valve.



6. Maintenance and Periodic Cleaning Operations

▲ WARNING

If the above-mentioned instructions are not adhered to the manufacturer cannot be held responsible for damage to persons or things.

WARNING

In order to prevent cracks or leakage: do not store or install the coffee machine in places where temperature may cause water in boiler or hydraulic system to freeze.

▲ WARNING

The machine is intended to be permanently connected to fixed wiring, and it is advisable that a residual current device (RCD) with a rated residual operating current not exceeding 30mA is installed.

WARNING

The machine must be installed so that qualified technical presonnel can easily access it for eventual maintenance.

WARNING

The machine must not be dipped in, nor splashed with, water in order to clean it. For cleaning operations, please follow the instructions listed below very carefully.

WARNING

Do not remove the filter holder while relative group is brewing hot liquids.

The Coffee Boiler contains water at elevated temperature. Water temperature over 125°F / 52°C can cause severe burns instantly or death from

scalding.

WARNING

This machine is for professional use only and should be installed in locations where its use and maintenance is restriced to trained personnel.

WARNING

Jets of water should not be used to clean the machine, nor should it be placed where water jets are used.

1) Cleaning groups and drain wells

- Put a tablespoon of detergent powder for coffee machines into the blind filter, supplied with the machine, and tighten it onto the group you want to clean by using a normal filter holder.
- Turn the Paddle Valve on and off approximately 10 times (10 seconds intervals) on each group.
- Rinse the group using a normal filter by running hot water through it several times.

Note: Do not perform the cleaning procedure when other groups are dispensing coffee.

2) Cleaning filters

- Put 2 or 3 teaspoons of detergent powder for coffee machines in about 1/2 a litre of water inside a heat-resistant container and holl
- Dip filters in the boiled solution and leave them fully submerged for about 30 minutes.
- Rinse thoroughly with clean water and run hot water through one group several times with the filters in place.
- Make one cup of coffee and discard in order to remove any unpleasant flavor.

3) Cleaning filter holders (portafilters)

Using the proper cleaning tool (brush) wash the filter holders under hot water, a neutral detergent may also be used.

4) Cleaning the drain collector

Remove the drain tray grill at least twice a week and clean, pull out the water drain collector and clean it thoroughly. Inspect and clean also the drain box and remove any leftover grounds.

5) Cleaning the body


Wipe the stainless steel surfaces with a soft, non abrasive cloth in the direction of the glazing marks, if any. Do not use any alcohol or solvents whatsoever on painted or imprinted parts in order not to damage them.

6) Cleaning the hot water and steam nozzles

Steam nozzles must be cleaned immediately after use with a damp cloth and by producing a short burst of steam so as to prevent the formation of deposits inside the nozzles themselves, which may alter the flavor of other drinks to be heated. Hot water nozzles must be cleaned periodically with a damp cloth.

7) Cleaning the diffuser screen

- Due to filter holder discharge operations (subsequent to coffee brewing), a certain amount of coffee grounds may slowly build-up on and obstruct, even partially, the diffuser screen. To clean it, you must first remove it by unscrewing the diffuser screw.



- Put 2 or 3 teaspoons of cleaning detergent for coffee machines in about 1/2 a litre of water inside a heat-resistant container and boil.
- Place the diffuser screen(s) and diffuser screw(s) in the solution and leave them fully submerged for about 30 minutes.

Rinse thoroughly with clean water. Install and run hot water through each group several times with the screen installed.

8) Water Filter/Softener

Please see the documentation accompanying the water filter/softener for proper operating and cleaning instructions.

• Steam boiler draining: to activate this function you need to access the programming menu (see p. 117). Yearly, we recommend to fully drain the steam boiler by means of the specific drain cock located on the side of the boiler or under the boiler.

9) Depressurize the steam boiler

Press and hold the button to set the espresso machine to "OFF", then turn the steam knob in order to depressurize the steam boiler.

IMPORTANT

If the machine has not been used for more than 8 hours or, in any case, after long periods of being idle, in order to use the machine to its full potential it is necessary to perform some cleaning cycles before brewing beverages as follows:

- Groups: with the portafilters engaged in the groups brew water through each for at least two minutes
- Being careful to avoid burns, turn on

each steam wand for at least one minute.

- Turn on the hot water valve for the time necessary to allow the following quantities of water to be brewed:

At least 1 liter for a 1/2 group machine At least 2 liters for a 3 group machine

If the machine is not going to be used for long periods of time, it is advisable to follow these safety indications:

- Disconnect the machine from the water mains or interrupt the water connection via a mains tap.
- Disconnect the machine from the electrical mains.

7. De-commissioning and Demolition

1) De-commissioning and demolition

Start by setting the main switch to the "0" or OFF position.

Disconnecting from the power outlet

Disconnect the espresso machine from the electrical network by switching off the associated circuit breaker or circuit protection device. Remove the power supply cord from the power connection. Remove the Pump Motor Power Cord from the water pump motor.

Disconnecting from the water system

Shut off the water supply by closing the specific tap located upstream of the water filter/softener inlet. Disconnect the water pipe at the water filter/softener inlet. Remove the hose connecting the espresso machine to the water pump. Remove

the reinforced plastic tubing on the drain connection.

At this point, the machine may be removed from the bar, being very careful not to drop it or squash your fingers.

The machine is made out of various materials and therefore, if you do not intend to put it back in service, it must be taken to a special disposal company which will select the materials which can be recycled and discard the others.

Current regulations make it illegal to discard such machine by leaving it on public grounds or on any private property.

Recycling notice: Warning for the protection of the environment.

Used Electrical and electronic waste contains hazardous but also valuable and scarce materials which should be recovered and recycled properly. We kindly ask that you contribute to the protection of the environment and natural resources by delivering used equipment to the relevant recycling locations if such locations are available in your country.



8. Mandatory Maintenance and Check-up Operations

These operations are in addition to the Maintenance and Periodic Cleaning Operations as specified in Chapter 6.

The following maintenance and check-up operations sould be carried out by a qualified technician.

The time required for the periodic maintenance is determinated by the quantity of daily work and/or coffee consumption.

N.B. These periodic maintenance operations are not covered by warranty.

- Check/note water quality (Water quality must be within the range of parameters specified in the chapter on Installation, otherwise warranty is voided)
- Replace group gaskets

- **EVERY THREF/FOUR MONTHS** Replace diffuser screens
- springs condition
- Inspect drain box and hose for leaks or clogs
- Check all buttons for proper operation

- Check brewing pressure
- Check filter baskets and Check expansion valve operation
 - Check flow-rate for each group
 - Check doses consistency (if AV)
 - Check steam valves for proper operation
- Check vacuum breakers for proper operation
- Clean auto-fill probes
- If ABR: run "scale test"

EVERY SIX MONTHS (in addition to the above)

- Replace filter baskets
- Fit steam valve rebuild kit
- If ABR: calibrate scales
- If ABR: check weight of precision portafilters

EVERY YEAR (in addition to the above)

- Inspect solenoid valves
- Replace vacuum breakers
- Inspect expansion valve
- Inspect electrical wiring condition
- Replace safety valve

- Inspect flowmeter impellers (if AV)
- Accurate control of the tightness at 2.4Nm of each cable on the terminal block.

EVERY 3 YEARS (in addition to the above)

• Check the condition of boilers and, if necessary, take them out for proper descaling.

9. Precision Scale

WARNING

Handle with care maximum load 1Kg do not lift.

WARNING


The individual grid of the scale is a fragile component, handle and store with care.

WARNING


The height of the bottom tray is fixed.

1) Use precautions


Remove the adhesive label with care: if needed, remove any adhesive residues from the surface using a neutral detergent.



Don't spill water onto the scale box If needed, gently remove it with an absorbent cloth. Should any water and/or dirt penetrate into the holes highlighted



in the figure below, gently clean and dry them with an absorbent paper cloth. Dirt build-up or water stagnation may prevent the scale individual grid from properly settling into place.



The weighing system in static conditions (*) has a rated accuracy of ±0.5g. For correct operation, make sure that:

- Maintenance is performed properly, by an authorized person and in the manner prescribed in this manual:
- Please use the machine according to the instructions specified in this manual:
- Please make sure the machine is installed on a level and firm counter:
- Please make sure the power supply is stable and without electrical noises.

The weighing stage is a inherently delicate, in fact it is affected by:

- Vibration of the bench caused for example by other devices;
- Machine vibrations caused, for example, by the use of the adjacent group.

(*) Static weighing means weighing an object whose weight is fixed during the entire weighing.

The machine is not a weighing device certified for legal weighing.

- The weighing system is a precision device that requires a lot of caution in terms of use, cleaning and maintenance.
- Should the main grid or tray be removed, ensure not to hit the load cells during the disassembly and reassembly operations.
- To proceed with the weighing of the filter holder either empty or filled with coffee powder, place it as shown below:



- Use only original La Marzocco filters and filter holders, identified by the following symbol:


- Use only filter holders with double spout;
- Do not place on the scale objects weighing more than 1kg;
- Never load more than 1 kg, to prevent any damage to the scales;
- Use the high precision scale with care, avoid shocks, falling objects and sudden load peaks;
- Any object to be weighed must be placed correctly on the scales grid.

2) Cleaning

- The cleaning of the "individual grids" must be performed with care, without overloading the cells;
- For proper weighing of the filter holder, make sure the grid is clean and dry;
- To avoid contact with dirt before placing the filter holder, clean and dry the grid;
- Please be careful during the cleaning procedures to avoid the water dripping on the scale and its electrical components;

- Don't wash the scale individual grids in a dishwasher; wash them manually instead, then immediately dry them.


If you wash the grid under a strong water flow, remove the magnetic support highlighted in the figure (just pull to detach the magnets). Make sure that the magnets are always dry and clean.




- To clean the drain tray you need to remove the individual grids (part 2, figure 3) first, then the drain grille (part 1, figure 3) and finally the tray (part 3, figure 3). Make sure not to hit the load cells during the disassembly and reassembly operations.

10. Software Programming Guide

"Barista" Programming





"Barista" Programming




Group Dose
Exit
page 55

"Technical" Programming





"Technical" Programming





Programming Introduction

Description

- This espresso machine has a CPU and many configurable settings.
- Additionally, there are many feedback controls employed in this espresso machine to troubleshoot problems should they occur.
- The following is a brief introduction to the controls and display and how they interact with the operator.

Digital Display



- Digital display
- 2 Name
- 3 Daily timetable
- 4 1st group coffee boiler temperature

- 5 2nd group coffee boiler temperature
- 6 3rd group coffee boiler temperature
- Steam Boiler
- Heating indicator (on during heating, off when the temperature has been reached)

The digital display is a backlit display capable of displaying 2 lines of 16 characters. The display enables the operator to interact with the espresso machine to visibly change parameter values. The display also provides valuable information to the operator.

There are several warnings that the can be displayed to alert the operator of an unusual condition or a fault. Additionally, simple messages are displayed alerting the operator that an action has been started or that a process needs to begin.


Programming AV Keypad



The keypad has two functions. The first is for control of the espresso. The second is for programming individual software parameters. The programming of the individual parameters is possible only using the buttons in the group 1 (group starting from the left).

par	This button is used to control the brewing of the single espresso. It is also used in the programming of the individual parameters such as the "back" button in the menu. For simplicity's sake in this manual it will be represented with the name T1.
ind	This button is used to control the brewing of the double espresso. It is also used in the programming of the individual parameters such as the "forward" button in the menu. For simplicity's sake in this manual it will be represented with the name T2.
par	This button is used to control the brewing of the single espresso. It is also used in the programming of the individual parameters such as the "enter" button in the menu. For simplicity's sake in this manual it will be represented with the name T3.

Programming EE Keypad



The keypad has two functions. The first is for control of the espresso. The second is for programming individual software parameters.

Button	Description
	This button is used to control the brewing of the group 1 espresso. It is also used in the programming of the individual parameters such as the "back" button in the menu. For simplicity's sake in this manual it will be represented with the name T1.
	This button is used to control the brewing of the group 2 espresso. It is also used in the programming of the individual parameters such as the "forward" button in the menu. For simplicity's sake in this manual it will be represented with the name T2.
	This button is used for a control of the brewing of the hot water. It is also used in the programming of the individual parameters such as the "enter" button in the menu. For simplicity's sake in this manual it will be represented with the name T3.

Turning the Espresso Machine On

OFF 00:00

Description

The following is the procedure to be followed for the first use of the espresso machine.

- Please follow the procedures carefully to avoid any damage to the espresso machine.
- Proceed checking for water connection to the espresso machine.
- Proceed making sure you have filled the boilers.

Display		Operating Procedure
	1	Turn the Main Switch to the 1 position.
SB FILLED?	2	To continue with the start up process, press the T3 button after filling the steam boiler.
GROUPS BLED?	3	To continue with the start up process, press the T3 button after the saturation of the coffee boiler.
94.4 00:00 95.5 95.1 SB	4	The rectangles next to CB and SB indicate the warming up of the water contained in the boilers. When the set temperature is reached, these rectangles turn off and all the lights of the buttons turn on. Now the machine is ready for use. During the normal operation of the machine, the flashing of the rectangles indicates the intermittent heating necessary for maintaining the temperature.
95.5 95.1 SB		NOTE: Ensure all air is removed from the group prior to staring the espresso machine. This only needs to be completed once during the initial setup or when water is drained from the coffee boiler. WARNING
		HAZARDOUS VOLTAGE DISCONNECT FROM POWER SUPPLY BEFORE SERVICING 35

Shut Down Procedures

Turning the Espresso Machine Off

OFF 00:00

Description

The following is the procedure for turning off power to the espresso machine.

- Please follow the procedures carefully to avoid any damage to the espresso machine.
- This machine has two off settings. One setting turns off all of the components in the espresso machine and the other turns off power to the complete espresso machine.

	Display	Operating Procedure		
		1 The following is the procedure for safely turning off the espresso machine.		
	94.4 00:00 95.5 95.1 SB	Press and hold the buttons T2 and T3 at the same time. The display changes to the following:		
	OFF 00:00	3 This is the OFF setting used in the normal operating conditions.		
		During servicing or other conditions that warrant it, the main switch should be turned to the 0 position.		
		The espresso machine is off and display should be blank. It is important to follow this procedure when turning off the machine. Failure to do so can damage the electronics.		
Ц		▲ WARNING A		
		HAZARDOUS VOLTAGE DISCONNECT FROM POWER		
. 3	36	SUPPLY BEFORE SERVICING		

Accessing Programming Mode

Programming Mode

- 94.4 00:00 95.5 95.1 SB
- To change the values of any parameter the operator must first enter into the programming mode.
- There are two levels within the programming mode that allow the programming of specific parameters.
- The two programming levels are as follows:
- Barista Programming The parameters contained within this level are ones the operator can change to affect the quality of the espresso.
 - No password is required for access.

Display	Operating Procedure
	"Barista" Programming Level
94.4 00:00 95.5 95.1 SB	While the espresso machine is on, press and hold the button . After approximately 5 seconds the following display appears.
Group Dose Settings AV version Water Dose Settings EE version	2 This is the "Barista" programming level. To program the brewing amount for each button, to set the coffee boilers, the pre-infusion, and to enable/disable the resistance of the cup warmer if present.
Exit Menu	To exit the programming mode, scroll to the exit menu, using the buttons T1 or T2. Press the T3 button to confirm the exit, or press at the same time the buttons T2 and T3.

Accessing Programming Mode

Programming Mode

Description

94.4 00:00 95.5 95.1 SB • Technical Programming - The parameters contained within this level are ones the operator can change to affect the performance of the espresso machine. These parameters are set in the factory and their adjustment requires the intervention of a service technician La Marzocco reccomends that no changes are made at this level. The Technician Password is required for access.

Display		Operating Procedure
94.4 00:00 95.5 95.1 SB	4	"Technical" Programming Level While the espresso machine is on, press and hold the button . After approximately 10 seconds the following display appears.
Enter Password ******	5	This is the "Technical" programming level. Enter the password and press the buttons T1 and T2 to move between the available parameters, press the T3 button to confirm. Note: You must scroll to the exit menu to exit the programming mode, or press at the same time the buttons T2 and T3.

Cleaning Cycles

Description

GR1 Backflushins

- This parameter allows the operator to carry out the washing of the coffee groups, in an automatic way, by running multiple cleaning cycles.
- This espresso machine has a group rinsing function (rinsing jets) integrated in the electronics.
- The rinsing procedure is provided to give the operator more flexibility and freedom with regard to this operation.
- Do not perform the cleaning procedure when other groups are dispensing coffee.

Display	Operating Procedure
GR1 Backflushing	When the espresso machine is on, to enable the washing procedure press and hold at the same time the buttons 1 T1 and the continuous button. This activates the washing procedure of each group.
	When activated, the water pump comes into operation, and the electric valve of the specific group being washed will turn on and off the cycle. There are about 10 preset cycles with an interval of 4 seconds. To manually stop the rinsing, press any key.
	NOTE: In order to properly rinse the groups, put a small amount of detergent in a blind portafilter basket and insert it in the group to be rinsed before activating the rinsing process.
	MOST DETERGENTS CAUSE FOAMING DURING THE CLEANING PROCESS. THIS FOAM COLLECTS AT THE DRAIN BOX AND CAN PROHIBIT WASTE WATER FROM DRAINING PROPERLY.

RINSING MULTIPLE GROUPS SIMULTANEOUSLY COULD CAUSE THE DRAIN BOX TO OVERFLOW.

Brewratio Programming (only on ABR espresso machine models)

Brewratio

PF 0s 0s 0.0 0.0 0.0

Description

The procedure for weighing the filter holder either empty or filled with coffee powder is shown below.

- This parameter records the values for the brew according to the brew ratio technology.
- These values can be changed even manually by entering the software settings.
- To brew in brew ratio mode, set this mode by entering the software settings.
- Brew ratio: this mode is the ratio between the coffee powder and the weight of the drink

Display	Operating Procedure
94.4 00:00 95.5 95.1 SB	1 When the espresso machine is on, press and hold the button 6 . After about 5 seconds the following screen is displayed.
PF 0s 0s 0.0 0.0 0.0	When the value is no longer flashing, place the empty filter holder on the appropriate seat of the grid as described in chapter 9. The value is automatically recorded. (*)
94.4 00:00 95.5 95.1 SB	3 Press and hold the button T1. After about 5 seconds the following screen is displayed.
COF 0s 0s 0s 0.0 0.0	 When the value is no longer flashing, place the filter holder filled with coffee powder on the appropriate seat of the grid as described in chapter 9. The value is automatically recorded. This procedure can be repeated for all the brewing groups. (*) This procedure must be performed at the first installation, though it is possible to repeat it anytime (for
	example if you get a new portafilter set).

Program Dose

Group Dose Settings Program Volume Dose

- This parameter allows the operator to program the amount of coffee (brewing amount) for each Selection Indicator.
- The brewing amount can be set in terms of time (sec.), pulses, mass or brewratio.
- Once programmed, the Selection Indicator remains lighted.
- It is possible to set the dose for both a short and a long shot on the same Selection Indicator.
- PULSE mode: control of doses in volume
- MASS mode: control of doses in mass
- BREW RATIO mode: ratio between the coffee powder and the weight of the drink

Display	Operating Procedure
94.4 00:00 95.5 95.1 SB	1 When the espresso machine is turned on, press and hold the button 6 to access the "Barista" programming. After about 5 seconds the following screen is displayed.
Group Dose Settings	2 Press the button T1 or T2 to display the following menu:
Program Volume Dose	3 Press the T3 button to start the doses programming procedure.

Group Dose Settings Program Volume Dose

- This parameter allows the operator to program the amount of coffee (brewing amount) for each Selection Indicator.
- The brewing amount can be set in terms of time (sec.), pulses, mass or brewratio.
- Once programmed, the Selection Indicator remains lighted.
- It is possible to set the dose for both a short and a long shot on the same Selection Indicator.
- PULSE mode: control of doses in volume
- MASS mode: control of doses in mass
- BREW RATIO mode: ratio between the coffee powder and the weight of the drink

Display	Operating Procedure
	On each button you can set two doses, one for a short shot, one for a long shot.
Press Enter To Exit	To set the brewing time of a short shot, press and release the button immediately, press again to stop and sto the desired dose.
Press b To Stop 10 pulses	To set the brewing time of a long shot, press and hold the button for about 2 seconds, press and release the button immediately to store the desired dose.
G1B1 Saved	The two doses of each key can be set independently from one another.
10 Pulses	If one of the two doses is not set or does not refer to the corresponding dose of the first group, it will work a continuous dose.
Press Enter To Exit	5 Press the T3 button to return to the doses programming.
Group Dose Exit	6 Press T1 or T2 to continue with the programming of the other parameters.

Program Dose

Group Dose Settings Program Mass Dose

- This parameter allows the operator to program the amount of coffee (brewing amount) for each Selection Indicator.
- The brewing amount can be set in terms of time (sec.), pulses, mass or brewratio.
- Once programmed, the Selection Indicator remains lighted.
- It is possible to set the dose for both a short and a long shot on the same Selection Indicator.
- PULSE mode: control of doses in volume
- MASS mode: control of doses in mass
- BREW RATIO mode: ratio between the coffee powder and the weight of the drink

Display	Operating Procedure
94.4 00:00 95.5 95.1 SB	When the espresso machine is turned on, press and hold the the button to access the "Barista" programming. After about 5 seconds the following screen is displayed.
Group Dose Settings	2 Press the button T1 or T2 to display the following menu:
Program Mass Dose	3 Press the T3 button to start the doses programming procedure.

"Barista" Programming (only on ABR espresso machine models)

Group Dose Settings Program Mass Dose

- This parameter allows the operator to program the amount of coffee (brewing amount) for each Selection Indicator.
- The brewing amount can be set in terms of time (sec.), pulses, mass or brewratio.
- Once programmed, the Selection Indicator remains lighted.
- It is possible to set the dose for both a short and a long shot on the same Selection Indicator.
- PULSE mode: control of doses in volume
- MASS mode: control of doses in mass
- BREW RATIO mode: ratio between the coffee powder and the weight of the drink

Display		Operating Procedure
		On each button you can set two doses, one for a short shot, one for a long shot.
Press Enter To Exit		To set the brewing time of a short shot, press and release the button immediately, press again to stop and store the desired dose.
Press b To Stop 20.09	4	To set the brewing time of a long shot, press and hold the button for about 2 seconds, press and release the button immediately to store the desired dose.
G1B1 Saved		The two doses of each key can be set independently from one another.
20.09		If one of the two doses is not set or does not refer to the corresponding dose of the first group, it will work as continuous dose.
Press Enter To Exit	5	Press the T3 button to return to the doses programming.
Group Dose Exit	6	Press T1 or T2 to continue with the programming of the other parameters.

Program Dose

Group Dose Settings G1 Doses Settings

- This parameter allows the operator to program the amount of coffee (brewing amount) for each Selection Indicator.
- The brewing amount can be set in terms of time (sec.), pulses, mass or brewratio.
- Once programmed, the Selection Indicator remains lighted.
- It is possible to set the dose for both a short and a long shot on the same Selection Indicator.
- PULSE mode: control of doses in volume
- MASS mode: control of doses in mass
- BREW RATIO mode: ratio between the coffee powder and the weight of the drink

Display	Operating Procedure
94.4 00:00 95.5 95.1 SB	1 When the espresso machine is turned on, press and hold the the button 6 to access the "Barista" programming. After about 5 seconds the following screen is displayed.
Group Dose Settinas	2 Press the button T1 or T2 to display the following menu:
G1 Doses Settings	3 Press the T3 button to start the doses programming procedure.
Group 1 Mode PULSES	4 Press the T3 button to access the menu, then navigate using T1 and T2 to choose between PULSES, MASS and BREWRATIO, press the T3 button to confirm the option.

Group Dose Settings 61 Doses Settings

- This parameter allows the operator to program the amount of coffee (brewing amount) for each button on the keyboard.
- The brewing amount can be set in terms of time (sec.) or pulses. This number refers to the number of pulses that the flowmeter sends to the CPU.
- Once programmed, the button remains lighted.

- It is possible to set the dose for both a short and a long shot on the same key.
- The setting of the first group is automatically copied to the subsequent groups.
- It is possible to set each key individually, in this case the dose of the first group will no longer be used.
- It is possible to copy the doses of any key to the others.

Display	Operating Procedure
G1B1 Dose 30 Pulses	Press the button T1 or T2 to view the dose. Pressing the button T3, the dose value will blink. Use the button T1 or T2 to change the value, press the button T3 to confirm the desired value.
G1 Doses Exit	6 Press the button T3 to exit the submenu.
Group Dose Exit	7 Press T1 or T2 until the display shows the exit menu, press the T3 button to return to the "Barista" programming.
	8 Press T1 or T2 to continue with the programming of the other parameters.

Program Dose

Group Dose Settings G1 Doses Settings

- This parameter allows the operator to program the amount of coffee (brewing amount) for each button on the keyboard.
- The brewing amount can be set in terms of time (sec.) or pulses. This number refers to the number of pulses that the flowmeter sends to the CPU.
- Once programmed, the button remains lighted.

- It is possible to set the dose for both a short and a long shot on the same key.
- The setting of the first group is automatically copied to the subsequent groups.
- It is possible to set each key individually, in this case the dose of the first group will no longer be used.
- It is possible to copy the doses of any key to the others.

	inginiod.
Display	Operating Procedure
94.4 00:00 95.5 95.1 SB	9 Press T2 and T3 at the same time to exit the programming mode and return to the normal use of the espresso machine.

"Barista" Programming (only on ABR espresso machine models)

Program Dose Scales

Group Dose Settinas G1 Doses Settinas

- This parameter allows the operator to view and manually change each dose for each key.
- For greater accuracy and consistency of the doses, it is recommended that you set each key.

Display	Operating Procedure
LaMarzocco 00:00 CB 93,8°C SB	1 When the espresso machine is turned on, press and hold the the button 6 to access the "Barista" programming. After about 5 seconds the following screen is displayed.
Group Dose Settings	2 Press the button T1 or T2 to display the following menu:
G1 Doses Settinas	3 Press the T3 button to start the doses programming procedure.
Group 1 Mode BREWRATIO	4 Press the T3 button to access the menu, then navigate using T1 and T2 to choose between PULSES, MASS and BREWRATIO, press the T3 button to confirm the option.

Program Dose Scales

Group Dose Settings G1 Doses Settings

- This parameter allows the operator to view and manually change each dose for each key.
- For greater accuracy and consistency of the doses, it is recommended that you set each key.

Display	Operating Procedure
G1B1 Brew Ratio 1:2.00	Press the button T1 or T2 to view the dose of each key. Pressing the button T3, the dose value will blink. Use the button T1 or T2 to change the value, press the button T3 to confirm the desired value.
G1 PF Mass 800.09	6 Press the button T1 or T2 to view the portafilter mass of each group. Pressing the button T3, the value will blink. Use the button T1 or T2 to change the value, press the button T3 to confirm the desired value.
G1 Coffee Mass 14.0s	7 Press the button T1 or T2 to view the coffee mass of each group. Pressing the button T3, the value will blink. Use the button T1 or T2 to change the value, press the button T3 to confirm the desired value.
G1B3 Mode CONTINUOUS	8 Press the button T3 to enter the menu, then navigate using T1and T2 to choose between CONTINUOUS or 3 SEC RINS.

"Barista" Programming (only on ABR espresso machine models)

Program Dose Scales

Group Dose Settinas G1 Doses Settinas

- This parameter allows the operator to view and manually change each dose for each key.
- For greater accuracy and consistency of the doses, it is recommended that you set each key.

Display	Operating Procedure
G1 Doses Exit	9 Press the button T3 to exit the submenu.
Group Dose Exit	10 Press T1 or T2 until the display shows the exit menu, press the T3 button to return to the "Barista" programming.
	11 Press T1 or T2 to continue with the programming of the other parameters.
94.4 00:00 95.5 95.1 SB	Press T2 and T3 at the same time to exit the programming mode and return to the normal use of the espresso machine.

Program Dose

Description

Group Dose
Settings
Copy Doses
By Button

 This parameter allows the operator to copy the doses present of each key to the others.

Display	Operating Procedure		
94.4 00:00 95.5 95.1 SB	1 When the espresso machine is turned on, press and hold the the button 6 to access the "Barista" programming. After about 5 seconds the following screen is displayed.		
Group Dose Settings	2 Press the button T1 or T2 to display the following menu:		
Copy Doses By Button	3 Press the button T3 to start the dose copy procedure.		
Push Button To Copy	4 Press the key whose setting you want to copy. Now all the keys will flash.		

Program Dose

Description

Group Dose Settings Cop

Cory Doses By Button • This parameter allows the operator to copy the doses present of each key to the others.

Display		Operating Procedure
Push to Paste B5 to Exit	5	Press the key where you want to paste the previously copied setting. Successful programming is indicated by the fixed lighting of the key. It is possible to repeat this procedure on any key.
Group Dose Exit	6	Press T1 or T2 until the display shows the exit menu, press the T3 button to return to the "Barista" programming.
	7	Press T1 or T2 to continue with the programming of the other parameters.
94.4 00:00 95.5 95.1 SB	8	Press T2 and T3 at the same time to exit the programming mode and return to the normal use of the espresso machine.

Program Dose

Description

Group Dose Settings Copy Doses By Group This parameter allows the operator to copy the doses present of each group to the others.

Display	Operating Procedure
94.4 00:00 95.5 95.1 SB	When the espresso machine is turned on, press and hold the the button to access the "Barista" programming. After about 5 seconds the following screen is displayed.
Group Dose Settings	2 Press the button T1 or T2 to display the following menu:
Copy Doses By Group	3 Press the button T3 to start the dose copy procedure.
Select Group To Copy	4 Press the key whose setting you want to copy. Now all the keys will flash.

Program Dose

Description

Group Dose Settinas

> Copy Doses By Group

• This parameter allows the operator to copy the doses present of each group to the others.

Display	Operating Procedure
Push to Paste B5 to Exit	Press the key where you want to paste the previously copied setting. Successful programming is indicated by the fixed lighting of the key. It is possible to repeat this procedure on any group.
Group Dose Exit	6 Press T1 or T2 until the display shows the exit menu, press the T3 button to return to the "Barista" programming.
	7 Press T1 or T2 to continue with the programming of the other parameters.
94.4 00:00 95.5 95.1 SB	8 Press T2 and T3 at the same time to exit the programming mode and return to the normal use of the espresso machine.

Program Dose

Description

 This parameter allows the operator to cancel all the doses set.

Group Dose Settings Reset Doses

Display	Operating Procedure		
94.4 00:00 95.5 95.1 SB	1 When the espresso machine is turned on, press and hold the the button 6 to access the "Barista" programming. After about 5 seconds the following screen is displayed.		
Group Dose Settings	2 Press the button T1 or T2 to display the following menu:		
Reset Doses Resettine Doses	Press the button T3 to confirm the procedure. Now all settings are cleared.		
Group Dose Exit	4 Press T1 or T2 until the display shows the exit menu, press the T3 button to return to the "Barista" programming.		

Group Dose Settings

Program Dose

Reset Doses

Description

• This parameter allows the operator to cancel all the doses set.

Operating Procedure		
5 Press T1 or T2 to continue with the programming of the other parameters.		
6 Press T2 and T3 at the same time to exit the programming mode and return to the normal use of the espresso machine.		

Backflush

Group Dose Settings Backflush INDIVIDUAL

- This parameter allows the operator to carry out the washing of the coffee groups, in an automatic way, by running multiple cleaning cycles.
- This espresso machine has a group rinsing function (rinsing jets) integrated in the electronics.
- The rinsing procedure is provided to give the operator more flexibility and freedom with regard to this operation.

- Do not perform the cleaning procedure when other groups are dispensing coffee.
- The operator can choose between single-group rinsing mode and all-group rinsing mode, the latter by activating all groups together.

Display	Operating Procedure
94.4 00:00 95.5 95.1 SB	1 When the espresso machine is turned on, press and hold the the button 6 to access the "Barista" programming. After about 5 seconds the following screen is displayed.
Group Dose Settings	2 Press the button T1 or T2 to display the following menu:
Backflush INDIVIDUAL	Press the T3 button to enter the menu, move between the parameters using the buttons T1 and T2 to select INDIVIDUAL or ALL TOGETHER, press the T3 button to confirm the option.
GR1 Backflushina	When the espresso machine is on, to enable the washing procedure press and hold at the same time the buttons 1 and the continuous button. This activates the washing procedure of each group.

Backflush Group Dose Settings Rackflush INDIVIDUAL

- This parameter allows the operator to carry out the washing of the coffee groups, in an automatic way, by running multiple cleaning cycles.
- This espresso machine has a group rinsing function (rinsing jets) integrated in the electronics.
- The rinsing procedure is provided to give the operator more flexibility and freedom with regard to this operation.

- Do not perform the cleaning procedure when other groups are dispensing coffee.
- The operator can choose between singlegroup rinsing mode and all-group rinsing mode, the latter by activating all groups together.

Dienloy		Operating Presedure
Display		Operating Procedure
	5	When activated, the water pump comes into operation, and the electric valve of the specific group being washed will turn on and off the cycle. There are about 10 preset cycles with an interval of 4 seconds. To manually stop the rinsing, press any key.
	6	NOTE: In order to properly rinse the groups, put a small amount of detergent in a blind portafilter basket and insert it in the group to be rinsed before activating the rinsing process.
Group Dose Exit	7	Press T1 or T2 until the display shows the exit menu, press the T3 button to return to the "Barista" programming.
		MOST DETERGENTS CAUSE FOAMING DURING THE CLEANING PROCESS. THIS FOAM COLLECTS AT THE DRAIN BOX AND CAN PROHIBIT WASTE WATER FROM DRAINING PROPERLY.
58		RINSING MULTIPLE GROUPS SIMULTANEOUSLY COULD CAUSE THE DRAIN BOX TO OVERFLOW.

Backflush

Group Dose Settings Backflush INDIVIDUAL

- This parameter allows the operator to carry out the washing of the coffee groups, in an automatic way, by running multiple cleaning cycles.
- This espresso machine has a group rinsing function (rinsing jets) integrated in the electronics.
- The rinsing procedure is provided to give the operator more flexibility and freedom with regard to this operation.

- Do not perform the cleaning procedure when other groups are dispensing coffee.
- The operator can choose between single-group rinsing mode and all-group rinsing mode, the latter by activating all groups together.

Display	Operating Procedure
	8 Press T1 or T2 to continue with the programming of the other parameters.
94.4 00:00 95.5 95.1 SB	9 Press T2 and T3 at the same time to exit the programming mode and return to the normal use of the espresso machine.

Water Dose

Description

Group Dose
Settings
Water Dose
Settings

• This parameter allows the operator to program the amount of water (brewing amount) for the hot water button.

• This feature can be enabled or disabled.

D	isplay		Operating Procedure
94.4 95.5	00:00 95.1 SB	1	When the espresso machine is turned on, press and hold the the button to access the "Barista" programming. After about 5 seconds the following screen is displayed.
11	oup Dose ettinss	2	Move between the parameters using the buttons T1 or T2 until the display shows:
	ter Dose ettinas	3	Press the T3 button to enter the menu.
11	ter Dose NABLED	4	Press the T3 button to enter the menu, move between the parameters using the buttons T1 and T2 to select ENABLED or DISABLED, press the T3 button to confirm the option.

Water Dose

- Group Dose Settings Water Dose Settings
- This parameter allows the operator to program the amount of water (brewing amount) for the hot water button.
- This feature can be enabled or disabled.

Display		Operating Procedure
Program Water Dose	5	Desired dose can be programmed using hot water button. Press the T3 button to start dose programming procedure.
Press Water Button To Stop Press Water Button To Program Water Dose Saved 5.0 Seconds	6	To program the brewing time, press the hot water button to start and then press it again to stop when the desired dose is achieved. Now the saved brewing time is displayed.
G1 Water Dose 5.0s	7	Press T1 or T2 to display the dose of the hot water button. Pressing the button T3, the dose value will blink. Use the button T1or T2 to change the value, press the button T3 to confirm the desired value.

Group Dose Settings Water Dose

Settinas

- This parameter allows the operator to program the amount of water (brewing amount) for the hot water button.
- This feature can be enabled or disabled.

Display	Operating Procedure
Water Dose Exit	8 Press T1 or T2 until the display shows the exit menu, press the T3 button to return to the "Barista" programming.
	9 Press T1 or T2 to continue with the programming of the other parameters.
94.4 00:00 95.5 95.1 SB	10 Press T2 and T3 at the same time to exit the programming mode and return to the normal use of the espresso machine.

Coffee Boiler

Description

Group Dose
Settings

Coffee Boiler
Settings

- This parameter allows the operator to enable/disable the coffee boiler.
- This parameter allows the operator to program the coffee boiler temperature.
 Each group can have a different programming.

Display		Operating Procedure
94.4 00:00 95.5 95.1 SB	1	When the espresso machine is turned on, press and hold the the button to access the "Barista" programming. After about 5 seconds the following screen is displayed.
Group Dose Settings	2	Move between the parameters using the buttons T1 or T2 until the display shows:
Coffee Boiler Settings	3	Press the T3 button to enter the menu.
Coffee Boiler 1 ENABLED	4	Press the T3 button to enter the menu, move between the parameters using the buttons T1 and T2 to select ENABLED or DISABLED, press the T3 button to confirm the option. In the case of option enabled you can set the following parameters.

Coffee Boiler

Description

Group Dose
Settings

Coffee Boiler
Settings

- This parameter allows the operator to enable/disable the coffee boiler.
- This parameter allows the operator to program the coffee boiler temperature.
 Each group can have a different programming.

Display		Operating Procedure
CB1 Temperature 93.1°C 93.3°C	5	Press the T3 button to enter the menu, move with the buttons T1 and T2 to set the desired temperature, press the T3 button to confirm the value. In the case of espresso machine a multiple boilers you can set the temperature also on the coffee boiler. The temperature indicated on the left is the actual temperature of the group while the temperature on the right is the set temperature.
Coffee Boiler Exit	6	Press T1 or T2 until the display shows the exit menu, press the T3 button to return to the "Barista" programming.
	7	Press T1 or T2 to continue with the programming of the other parameters.
94.4 00:00 95.5 95.1 SB	8	Press T2 and T3 at the same time to exit the programming mode and return to the normal use of the espresso machine.

Pre-Infusion or Pre-Brewing

Group Dose Settings Preinfusion Settings

Description

- This parameter allows the operator to program the time of pre-brewing of water with the coffee. Each group can have a different programming.
- Pre-brewing has only two values to be adjusted for each group. The time (in seconds) for which the brewing valve is open during the pre-brewing cycle and the time (in seconds) for which the brewing valve is closed during the

pre-brewing cycle; during this time the pump is active. Once the pre-brewing cycle is over, the normal brewing cycle will continue until the end

• For an espresso machine composed of three groups, they are identified as Group 1, Group 2 and Group 3.

Display	Operating Procedure	
94.4 00:00 95.5 95.1 SB	1 When the espresso machine is turned on, press and hold the the button 6 to access the "Barista" programming. After about 5 seconds the following screen is displayed.	
Group Dose Settings	2 Move between the parameters using the buttons T1 or T2 until the display shows:	
Preinfusion Settings	3 Press the T3 button to enter the menu.	
Group 1 Pre-Inf 0s Wet Group 1 Pre-Inf 0s Hold	Press T1 or T2 to select the group whose parameters you want to set. 4 By pressing the T3 button the first value will blink. Use the buttons T1 and T2 to reach the value that you want to set, press T3 to confirm. Repeat this operation to set the second value.	

Pre-Infusion or Pre-Brewing

Group Dose Settings Preinfusion Settings

- This parameter allows the operator to program the time of pre-brewing of water with the coffee. Each group can have a different programming.
- Pre-brewing has only two values to be adjusted for each group. The time (in seconds) for which the brewing valve is open during the pre-brewing cycle and the time (in seconds) for which the brewing valve is closed during the
- pre-brewing cycle; during this time the pump is active. Once the pre-brewing cycle is over, the normal brewing cycle will continue until the end
- For an espresso machine composed of three groups, they are identified as Group 1, Group 2 and Group 3.

Display	Operating Procedure
Preinfusion Exit	5 Press T1 or T2 until the display shows the exit menu, press the T3 button to return to the "Barista" programming.
	6 Press T1 or T2 to continue with the programming of the other parameters.
94.4 00:00 95.5 95.1 SB	7 Press T2 and T3 at the same time to exit the programming mode and return to the normal use of the espresso machine.

Cup Warmer

Description

Group Dose
Settings
Cup Warmer
ENABLED

- This parameter allows the operator to enable or disable the cups heating function.
- This function is displayed only on the models of espresso machine equipped with this accessory.

Display	Operating Procedure
94.4 00:00 95.5 95.1 SB	When the espresso machine is turned on, press and hold the the button to access the "Barista" programming. After about 5 seconds the following screen is displayed.
Group Dose Settings	2 Move between the parameters using the buttons T1 or T2 until the display shows:
Cur Warmer ENABLED	Press the T3 button to enter the menu, move between the parameters using the buttons T1 and T2 to select ENABLED or DISABLED, press the T3 button to confirm the option.
	4 Press T1 or T2 to continue with the programming of the other parameters.

Cup Warmer

Group Dose Settinas Cup Warmer ENABLED

• This parameter allows the operator to enable or disable the cups heating function.

Description

• This function is displayed only on the models of espresso machine equipped with this accessory.

Display	Operating Procedure		
94.4 00:00 95.5 95.1 SB	5 Press T2 and T3 at the same time to exit the programming mode and return to the normal use of the espress machine.		

Barista Lights

Barista Lights Settings

Group Dose

Settinas

• This parameter allows the operator to adjust the brightness of the barista lights.

Description

• This parameter allows the operator to set up the brightness to be maintained in case of a temporary non utilization of the espresso machine.

Display	Operating Procedure	
94.4 00:00 95.5 95.1 SB	When the espresso machine is turned on, press and hold the the button to access the "Barista" programming. After about 5 seconds the following screen is displayed.	
Group Dose Settings	2 Move between the parameters using the buttons T1 or T2 until the display shows:	
Barista Lishts Settinss	3 Press the T3 button to enter the menu.	
Not Brewins	4 Press the T3 button to enter the menu, move with the buttons T1 and T2 to set the desired value, press the T3 button to confirm the value.	

Barista Lights

Description

Group Dose
Settings
Barista Lights
Settings

- This parameter allows the operator to adjust the brightness of the barista lights.
- This parameter allows the operator to set up the brightness to be maintained in case of a temporary non utilization of the espresso machine.

Display		Operating Procedure
Brewins 100,0 %	5	Press the T3 button to enter the menu, move with the buttons T1 and T2 to set the desired value, press the T3 button to confirm the value.
Eco Mode 5 %	6	Press the T3 button to enter the menu, move with the buttons T1 and T2 to set the desired value, press the T3 button to confirm the value.
Barista Lishts Exit	7	Press T1 or T2 until the display shows the exit menu, press the T3 button to return to the "Barista" programming.
94.4 00:00 95.5 95.1 SB	8	Press T2 and T3 at the same time to exit the programming mode and return to the normal use of the espresso machine.

Exit Menu

Group Dose Settings Menu Press B3 to Exit

Description

 This parameter allows the operator to exit the "Barista" programming and return to the normal use of the espresso machine.

Display	Operating Procedure	
Menu Press B3 to Exit	Press the T3 button to exit the "Barista" programming and return to the normal use of the espresso machine.	
94.4 00:00 95.5 95.1 SB	2 Alternatively, you can exit the "Barista" programming and return to the normal use of the espresso machine by pressing T2 and T3 at the same time.	

"Technical" Programming

Language

Description

• This parameter allows the technician to change the language of the display.

Enter Password

Language

ENGLISH

Display	Operating Procedure	
94.4 00:00 95.5 95.1 SB	1 When the espresso machine is turned on, press and hold the button . After about 10 seconds the following screen is displayed.	
Enter Password ******	2 Enter the technician password using the buttons T1, T2 and T3. After the acceptance, the following screen is displayed.	
Lanauage ENGLISH	3 Press the T3 button to enter the menu, move between the parameters using the buttons T1 and T2 to select a language, press the T3 button to confirm the option.	
	4 Press T1 or T2 to continue with the programming of the other parameters.	

Language

Description

Enter Password

Language

ENGLISH

• This parameter allows the technician to change the language of the display.

Display	Operating Procedure
Menu Press B3 to Exit	To exit the menu move between the parameters using the buttons T1 and T2 until the exit menu is displayed. Press the T3 button to exit the menu and return to the normal use of the espresso machine.
94.4 00:00 95.5 95.1 SB	6 Alternatively, you can exit the "Technical" programming and return to the normal use of the espresso machine by pressing T2 and T3 at the same time.

Temperature Measurement Units

Description

Enter Password

Temp Units
CELSIUS

 This parameter allows the technician to change the temperature display from degrees Celsius to degrees Fahrenheit and vice versa.

Display	Operating Procedure	
Enter Password ******	After accessing the "Technical" programming menu and entering the password, use the button until the following screen is displayed.	s T1 and T2
Temp Units CELSIUS	Press the T3 button to enter the menu, move between the parameters using the buttons T1 and an option, press the T3 button to confirm the option.	Γ2 to select
	Press T1 or T2 to continue with the programming of the other parameters.	
Menu Press B3 to Exit	To exit the menu move between the parameters using the buttons T1 and T2 until the exit menu Press the T3 button to exit the menu and return to the normal use of the espresso machine.	is displayed.

Temperature Measurement Units

Description

Enter Password

Temp Units

CELSIUS

 This parameter allows the technician to change the temperature display from degrees Celsius to degrees Fahrenheit and vice versa.

Display	Operating Procedure
94.4 00:00 95.5 95.1 SB	Alternatively, you can exit the "Technical" programming and return to the normal use of the espresso machine by pressing T2 and T3 at the same time.

Name Enter Password ****** Name LaMarzocco

- This parameter allows the technician to program a 16 character user name.
- The user name is displayed continuously on the display on the second line.

Display	Operating Procedure
Enter Password ******	1 After accessing the "Technical" programming menu and entering the password, use the buttons T1 and T2 until the following screen is displayed.
Name LaMarzocco	Press the T3 button to enter the menu, use the buttons T1 and T2 to set the desired value, press the T3 button to confirm the value and proceed with writing.
	3 Press T1 or T2 to continue with the programming of the other parameters.
Menu Press B3 to Exit	To exit the menu move between the parameters using the buttons T1 and T2 until the exit menu is displayed. Press the T3 button to exit the menu and return to the normal use of the espresso machine.

Name

- Enter Password

 Name

 LaMarzocco
- This parameter allows the technician to program a 16 character user name.
- The user name is displayed continuously on the display on the second line.

Display	Operating Procedure
94.4 00:00 95.5 95.1 SB	Alternatively, you can exit the "Technical" programming and return to the normal use of the espresso machine by pressing T2 and T3 at the same time.

Group Dose Settings Program Volume Dose

Program Dose

- This parameter allows the technician to program the amount of coffee (brewing amount) for each Selection Indicator.
- The brewing amount can be set in terms of time (sec.), pulses, mass or brewratio.
- Once programmed, the Selection Indicator remains lighted.
- It is possible to set the dose for both a short and a long shot on the same Selection Indicator.
- PULSE mode: control of doses in volume
- MASS mode: control of doses in mass
- BREW RATIO mode: ratio between the coffee powder and the weight of the drink

Display	Operating Procedure
Enter Password ******	1 After accessing the "Technical" programming menu and entering the password, use the buttons T1 and T2 until the following screen is displayed.
Group Dose Settings	2 Press the button T1 or T2 to display the following menu:
Program Volume Dose	3 Press the T3 button to start the doses programming procedure.

Program Dose

Group Dose Settings Program Volume Dose

- This parameter allows the technician to program the amount of coffee (brewing amount) for each Selection Indicator.
- The brewing amount can be set in terms of time (sec.), pulses, mass or brewratio.
- Once programmed, the Selection Indicator remains lighted.
- It is possible to set the dose for both a short and a long shot on the same Selection Indicator.
- PULSE mode: control of doses in volume
- MASS mode: control of doses in mass
- BREW RATIO mode: ratio between the coffee powder and the weight of the drink

Display	Operating Procedure
	On each button you can set two doses, one for a short shot, one for a long shot.
Press Enter To Exit	To set the brewing time of a short shot, press and release the button immediately, press again to stop and store the desired dose.
Press b To Stop 10 pulses	To set the brewing time of a long shot, press and hold the button for about 2 seconds, press and release the button immediately to store the desired dose.
G1B1 Saved	The two doses of each key can be set independently from one another.
10 Pulses	If one of the two doses is not set or does not refer to the corresponding dose of the first group, it will work as continuous dose.
Press Enter To Exit	5 Press the T3 button to return to the doses programming.
Group Dose Exit	6 Press T1 or T2 to continue with the programming of the other parameters.

"Technical" Programming (only on ABR espresso machine models)

Group Dose Settings Program Mass Dose

- This parameter allows the technician to program the amount of coffee (brewing amount) for each Selection Indicator.
- The brewing amount can be set in terms of time (sec.), pulses, mass or brewratio.
- Once programmed, the Selection Indicator remains lighted.
- It is possible to set the dose for both a short and a long shot on the same Selection Indicator.
- PULSE mode: control of doses in volume
- MASS mode: control of doses in mass
- BREW RATIO mode: ratio between the coffee powder and the weight of the drink

Display	Operating Procedure
Enter Password ******	1 After accessing the "Technical" programming menu and entering the password, use the buttons T1 and T2 until the following screen is displayed.
Group Dose Settings	2 Press the button T1 or T2 to display the following menu:
Program Mass Dose	3 Press the T3 button to start the doses programming procedure.

Program Dose

Group Dose Settings Program Mass Dose

- This parameter allows the technician to program the amount of coffee (brewing amount) for each Selection Indicator.
- The brewing amount can be set in terms of time (sec.), pulses, mass or brewratio.
- Once programmed, the Selection Indicator remains lighted.
- It is possible to set the dose for both a short and a long shot on the same Selection Indicator.
- PULSE mode: control of doses in volume
- MASS mode: control of doses in mass
- BREW RATIO mode: ratio between the coffee powder and the weight of the drink

Display	Operating Procedure
	On each button you can set two doses, one for a short shot, one for a long shot.
Press Enter To Exit	To set the brewing time of a short shot, press and release the button immediately, press again to stop and store the desired dose.
Press b To Stop 20.09	To set the brewing time of a long shot, press and hold the button for about 2 seconds, press and release the button immediately to store the desired dose.
G1B1 Saved	The two doses of each key can be set independently from one another.
20.09	If one of the two doses is not set or does not refer to the corresponding dose of the first group, it will work as continuous dose.
Press Enter To Exit	5 Press the T3 button to return to the doses programming.
Group Dose Exit	6 Press T1 or T2 to continue with the programming of the other parameters.

Group Dose Settings 61 Doses Settings

- This parameter allows the technician to program the amount of coffee (brewing amount) for each Selection Indicator.
- The brewing amount can be set in terms of time (sec.), pulses, mass or brewratio.
- Once programmed, the Selection Indicator remains lighted.
- It is possible to set the dose for both a short and a long shot on the same Selection Indicator.
- PULSE mode: control of doses in volume
- MASS mode: control of doses in mass
- BREW RATIO mode: ratio between the coffee powder and the weight of the drink

Display	Operating Procedure
Enter Password ******	1 After accessing the "Technical" programming menu and entering the password, use the buttons T1 and T2 until the following screen is displayed.
Group Dose Settinas	2 Press the button T1 or T2 to display the following menu:
61 Doses Settinas	3 Press the T3 button to start the doses programming procedure.
Group 1 Mode PULSES	4 Press the T3 button to access the menu, then navigate using T1 and T2 to choose between PULSES, MASS and BREWRATIO, press the T3 button to confirm the option.

Program Dose


Group Dose Settings G1 Doses Settings

- This parameter allows the technician to program the amount of coffee (brewing amount) for each button on the keyboard.
- The brewing amount can be set in terms of time (sec.) or pulses. This number refers to the number of pulses that the flowmeter sends to the CPU.
- Once programmed, the button remains lighted.

- It is possible to set the dose for both a short and a long shot on the same key.
- The setting of the first group is automatically copied to the subsequent groups.
- It is possible to set each key individually, in this case the dose of the first group will no longer be used.
- It is possible to copy the doses of any key to the others.

Diamlan	
Display	Operating Procedure
G1B1 Dose 30 Pulses	Press the button T1 or T2 to view the dose. Pressing the button T3, the dose value will blink. Use the button T1 or T2 to change the value, press the button T3 to confirm the desired value.
G1 Doses Exit	6 Press the button T3 to exit the submenu.
Group Dose Exit	7 Press T1 or T2 until the display shows the exit menu, press the T3 button to return to the "Technical" programming.
	8 Press T1 or T2 to continue with the programming of the other parameters.

Program Dose



- This parameter allows the technician to program the amount of coffee (brewing amount) for each button on the keyboard.
- The brewing amount can be set in terms of time (sec.) or pulses. This number refers to the number of pulses that the flowmeter sends to the CPU.
- Once programmed, the button remains lighted.

- It is possible to set the dose for both a short and a long shot on the same key.
- The setting of the first group is automatically copied to the subsequent groups.
- It is possible to set each key individually, in this case the dose of the first group will no longer be used.
- It is possible to copy the doses of any key to the others.

Display	Operating Procedure
94.4 00:00 95.5 95.1 SB	9 Press T2 and T3 at the same time to exit the programming mode and return to the normal use of the espresso machine.

Program Dose Scales

Group Dose Settings 61 Doses Settings

- This parameter allows the technician to view and manually change each dose for each key.
- For greater accuracy and consistency of the doses, it is recommended that you set each key.

Display	Operating Procedure
Enter Password ******	1 After accessing the "Technical" programming menu and entering the password, use the buttons T1 and T2 until the following screen is displayed.
Group Dose Settings	2 Press the button T1 or T2 to display the following menu:
G1 Doses Settings	3 Press the T3 button to start the doses programming procedure.
Group 1 Mode BREWRATIO	4 Press the T3 button to access the menu, then navigate using T1 and T2 to choose between PULSES, MASS and BREWRATIO, press the T3 button to confirm the option.

"Technical" Programming (only on ABR espresso machine models)

Program Dose Scales Group Dose

Settings G1 Doses

Settinas

- This parameter allows the technician to view and manually change each dose for each key.
- For greater accuracy and consistency of the doses, it is recommended that you set each key.

Display	Operating Procedure
G1B1 Brew Ratio 1:2.00	Press the button T1 or T2 to view the dose of each key. Pressing the button T3, the dose value will blink. Use the button T1 or T2 to change the value, press the button T3 to confirm the desired value.
G1 PF Mass 800.09	6 Press the button T1 or T2 to view the portafilter mass of each group. Pressing the button T3, the value will blink. Use the button T1 or T2 to change the value, press the button T3 to confirm the desired value.
G1 Coffee Mass	Press the button T1 or T2 to view the coffee mass of each group. Pressing the button T3, the value will blink. Use the button T1 or T2 to change the value, press the button T3 to confirm the desired value.
G1B3 Mode CONTINUOUS	8 Press the button T3 to enter the menu, then navigate using T1and T2 to choose between CONTINUOUS or 3 SEC RINS.

Program Dose Scales

Group Dose Settings G1 Doses Settings

- This parameter allows the technician to view and manually change each dose for each key.
- For greater accuracy and consistency of the doses, it is recommended that you set each key.

Display	Operating Procedure
G1 Doses Exit	9 Press the button T3 to exit the submenu.
Group Dose Exit	Press T1 or T2 until the display shows the exit menu, press the T3 button to return to the "Technical" programming.
	11 Press T1 or T2 to continue with the programming of the other parameters.
94.4 00:00 95.5 95.1 SB	Press T2 and T3 at the same time to exit the programming mode and return to the normal use of the espresso machine.

Program Dose

Description

Group Dose Settings

Cory Doses By Button This parameter allows the technician to copy the doses present of each key to the others.

Display	Operating Procedure
Enter Password ******	1 After accessing the "Technical" programming menu and entering the password, use the buttons T1 and T2 until the following screen is displayed.
Group Dose Settings	2 Press the button T1 or T2 to display the following menu:
Copy Doses By Button	3 Press the button T3 to start the dose copy procedure.
Push Button To Copy	4 Press the key whose setting you want to copy. Now all the keys will flash.

Program Dose

Description

Group Dose
Settings
Copy Doses
By Button

 This parameter allows the technician to copy the doses present of each key to the others.

Display	Operating Procedure
Push to Paste B5 to Exit	5 Press the key where you want to paste the previously copied setting. Successful programming is indicated by the fixed lighting of the key. It is possible to repeat this procedure on any key.
Group Dose Exit	6 Press T1 or T2 until the display shows the exit menu, press the T3 button to return to the "Barista" programming.
	7 Press T1 or T2 to continue with the programming of the other parameters.
94.4 00:00 95.5 95.1 SB	8 Press T2 and T3 at the same time to exit the programming mode and return to the normal use of the espresso machine.

Program Dose

Description

Group Dose
Settings

Copy Doses
By Group

• This parameter allows the technician to copy the doses present of each group to the others.

Display	Operating Procedure
Enter Password ******	1 After accessing the "Technical" programming menu and entering the password, use the buttons T1 and T2 until the following screen is displayed.
Group Dose Settings	2 Press the button T1 or T2 to display the following menu:
Copy Doses By Group	3 Press the button T3 to start the dose copy procedure.
Select Group To Copy	4 Press the key whose setting you want to copy. Now all the keys will flash.

Program Dose

Description

Group Dose
Settings

Copy Doses
By Group


 This parameter allows the technician to copy the doses present of each group to the others.

Display	Operating Procedure
Push to Paste B5 to Exit	5 Press the key where you want to paste the previously copied setting. Successful programming is indicated by the fixed lighting of the key. It is possible to repeat this procedure on any group.
Group Dose Exit	6 Press T1 or T2 until the display shows the exit menu, press the T3 button to return to the "Technical" programming.
	7 Press T1 or T2 to continue with the programming of the other parameters.
94.4 00:00 95.5 95.1 SB	8 Press T2 and T3 at the same time to exit the programming mode and return to the normal use of the espresso machine.

Program Dose

Description

• This parameter allows the technician to cancel all the doses set.



Display	Operating Procedure
Enter Password ******	1 After accessing the "Technical" programming menu and entering the password, use the buttons T1 and T2 until the following screen is displayed.
Group Dose Settings	2 Press the button T1 or T2 to display the following menu:
Reset Doses Resettins Doses	Press the button T3 to confirm the procedure. Now all settings are cleared.
Group Dose Exit	4 Press T1 or T2 until the display shows the exit menu, press the T3 button to return to the "Technical" programming.

Program Dose

Description

Group Dose
Settings

Reset
Doses

• This parameter allows the technician to cancel all the doses set.

Display		Operating Procedure
	5	Press T1 or T2 to continue with the programming of the other parameters.
94.4 00:00 95.5 95.1 SB	6	Press T2 and T3 at the same time to exit the programming mode and return to the normal use of the espresso machine.

Enter Password ****** Backflush INDIVIDUAL

- This parameter allows the operator to carry out the washing of the coffee groups, in an automatic way, by running multiple cleaning cycles.
- This espresso machine has a group rinsing function (rinsing jets) integrated in the electronics.
- The rinsing procedure is provided to give the operator more flexibility and freedom with regard to this operation.

- Do not perform the cleaning procedure when other groups are dispensing coffee.
- The operator can choose between single-group rinsing mode and all-group rinsing mode, the latter by activating all groups together.

Display	Operating Procedure
Enter Password ******	1 After accessing the "Technical" programming menu and entering the password, use the buttons T1 and T2 until the following screen is displayed.
Backflush INDIVIDUAL	2 Press the T3 button to enter the menu, move between the parameters using the buttons T1 and T2 to select INDIVIDUAL or ALL TOGETHER, press the T3 button to confirm the option.
GR1 Backflushing	When the espresso machine is on, to enable the washing procedure press and hold at the same time the buttons T1 and the continuous button. This activates the washing procedure of each group.
	When activated, the water pump comes into operation, and the electric valve of the specific group being washed will turn on and off the cycle. There are about 10 preset cycles with an interval of 4 seconds. To manually stop the rinsing, press any key.

Backflush

Enter Password ****** Backflush INDIVIDUAL

Description

- This parameter allows the operator to carry out the washing of the coffee groups, in an automatic way, by running multiple cleaning cycles.
- This espresso machine has a group rinsing function (rinsing jets) integrated in the electronics.
- The rinsing procedure is provided to give the operator more flexibility and freedom with regard to this operation.

- Do not perform the cleaning procedure when other groups are dispensing coffee.
- The operator can choose between single-group rinsing mode and all-group rinsing mode, the latter by activating all groups together.

Display	Operating Procedure	
	NOTE: In order to properly rinse the groups, put a small amount of detergent in a blind portafilter basket a insert it in the group to be rinsed before activating the rinsing process.	and
	6 Press T1 or T2 to continue with the programming of the other parameters.	
Menu Press B3 to Exit	7 To exit the menu move between the parameters using the buttons T1 and T2 until the exit menu is displayed. Press the T3 button to exit the menu and return to the normal use of the espresso machine.	ed.
	MOST DETERGENTS CAUSE FOAMING DURING THE CLEANING PROCESS. THIS FOAM COLLECTS AT THE DRAIN BOX AND CAN PROHIBIT WASTE WATER FROM DRAINING PROPERLY.	

RINSING MULTIPLE GROUPS SIMULTANEOUSLY COULD CAUSE THE DRAIN BOX TO OVERFLOW.

Backflush Enter Password ******

Backflush

INDIVIDUAL

- This parameter allows the operator to carry out the washing of the coffee groups, in an automatic way, by running multiple cleaning cycles.
- This espresso machine has a group rinsing function (rinsing jets) integrated in the electronics.
- The rinsing procedure is provided to give the operator more flexibility and freedom with regard to this operation.

- Do not perform the cleaning procedure when other groups are dispensing coffee.
- The operator can choose between singlegroup rinsing mode and all-group rinsing mode, the latter by activating all groups together.

Display	Operating Procedure
94.4 00:00 95.5 95.1 SB	8 Alternatively, you can exit the "Technical" programming and return to the normal use of the espresso machine by pressing T2 and T3 at the same time.


Crono Function

Enter Password ****** Chrono ENABLED

- When enabled, this parameter displays a timer that times each shot.
- The timer is reset each time a button on the keypad is pressed.
- If enabled, the Chrono function is permanently displayed during brewing, while during wait state it alternates with the programmable name.

Display	Operating Procedure
Enter Password ******	After accessing the "Technical" programming menu and entering the password, use the buttons T1 and T2 until the following screen is displayed.
Chrono ENABLED	Press the T3 button to enter the menu, move between the parameters using the buttons T1 and T2 to select ENABLED or DISABLED, press the T3 button to confirm the option.
Chrono Info Type TIME	3 Press the T3 button to enter the menu, move between the parameters using the buttons T1 and T2 to select an option (TIME/DOSE), press the T3 button to confirm the option.
GR1 GR2 GR3 18 0 0	4 In the case of active option (TIME or DOSE) the display shown to the side appears.

Crono Function



- When enabled, this parameter displays a timer that times each shot.
- The timer is reset each time a button on the keypad is pressed.
- If enabled, the Chrono function is permanently displayed during brewing, while during wait state it alternates with the programmable name.

Display	Operating Procedure
	5 Press T1 or T2 to continue with the programming of the other parameters.
Menu Press B3 to Exit	To exit the menu move between the parameters using the buttons T1 and T2 until the exit menu is displayed. Press the T3 button to exit the menu and return to the normal use of the espresso machine.
94.4 00:00 95.5 95.1 SB	7 Alternatively, you can exit the "Technical" programming and return to the normal use of the espresso machine by pressing T2 and T3 at the same time.

Water Dose

Description

Enter Password

Water Dose

Settings

- This parameter allows the operator to program the amount of water (brewing amount) for the hot water button.
- This feature can be enabled or disabled.

Display	Operating Procedure
Enter Password ******	1 After accessing the "Technical" programming menu and entering the password, use the buttons T1 and T2 until the following screen is displayed.
Water Dose Settings	2 Press the T3 button to enter the menu.
Water Dose WITH PUMP	3 Press the T3 button to enter the menu, move between the parameters using the buttons T1 and T2 to select WITH PUMP or WITHOUT PUMP, press the T3 button to confirm the option.
Water Dose ENABLED	4 Press the T3 button to enter the menu, move between the parameters using the buttons T1 and T2 to select ENABLED or DISABLED, press the T3 button to confirm the option.

Water Dose

Description

Enter Password

Water Dose Settinas • This parameter allows the operator to program the amount of water (brewing amount) for the hot water button.

• This feature can be enabled or disabled.

Display

Operating Procedure

Program Water Dose **5** Desired dose can be programmed using hot water button. Press the T3 button to start dose programming procedure.

Program
Water Dose
Press Water Button
To Stop
Press Water Button
To Program
Water Dose Saved

5.0 Seconds

To program the brewing time, press the hot water button to start and then press it again to stop when the desired dose is achieved.

Now the saved brewing time is displayed.

61 Water Dose 5.0s Press T1 or T2 to display the dose of the hot water button. Pressing the button T3 button, the dose value will blink. Use the button T1 or T2 to change the value, press the button T3 button to confirm the desired value.

Water Dose

- Enter Password

 Water Dose

 Settings
- This parameter allows the operator to program the amount of water (brewing amount) for the hot water button.
- This feature can be enabled or disabled.

Display	Operating Procedure
Water Dose Exit	8 Press the T3 button to return to the "Technical" programming.
	9 Press T1 or T2 to continue with the programming of the other parameters.
Menu Press B3 to Exit	To exit the menu move between the parameters using the buttons T1 and T2 until the exit menu is displayed. Press the T3 button to exit the menu and return to the normal use of the espresso machine.
94.4 00:00 95.5 95.1 SB	Alternatively, you can exit the "Technical" programming and return to the normal use of the espresso machine by pressing T2 and T3 at the same time.

"Technical" Programming (only on ABR espresso machine models)

Enter Password ****** Scale Configuration

- This parameter enables the technician to set some scale parameters like:
 - Enabling/disabling the offset parameter;
 - Setting the weight reading time;
 - Calibrating the scales;
 - Updating the scale software.

Display	Operating Procedure
Enter Password ******	1 After accessing the "Technical" programming menu and entering the password, use the buttons T1 and T2 until the following screen is displayed.
Scale Configuration	2 Press the T3 button to enter the menu.
Auto Offset ENABLED	Press the T3 button to enter the menu, move between the parameters using the buttons T1 and T2 to select ENABLED or DISABLED, press the T3 button to confirm the option.
Scale Tare Time	4 Press the T3 button to enter the menu, navigate the parameters using the buttons T1 and T2 to set the desired value. This parameter is common to all groups.

Program Scales

Enter Password ***** Scale Configuration

- This parameter enables the technician to set some scale parameters like:
 - Enabling/disabling the offset parameter;
 - Setting the weight reading time;
 - Calibrating the scales;
 - Updating the scale software.

Dis	splay		Operating Procedure
	Scale ESENT	5	This parameter indicates that the scale is properly connected; navigate using the T1 and T2 buttons to display the next menu.
	ibrate Scale	6	Press the T3 button to start the calibration procedure.
And Pre	G1 Scale ess Enter 009 on G1 ess Enter	7	Remove any object from the scale, then press the T3 button to confirm. Place the reference weights onto the scale, then press the T3 button to confirm. At the end of the process, the self-calibration values or a confirmation message are displayed. Repeat this operation for each group.
	e: v0.0.0 : to 0.0.0	8	Press T2 to proceed with setting and press the T3 button to update the scale firmware if necessary.

"Technical" Programming (only on ABR espresso machine models)

Enter Password ****** Scale Settinss

- This parameter enables the technician to set some scale parameters like:
 - Enabling/disabling the offset parameter;
 - Setting the weight reading time;
 - Calibrating the scales;
 - Updating the scale software.

Display	Operating Procedure
Start Scale Testins 0.0 0.0 0.0 Enter to Exit	9 Press the T3 button to enter the menu and place the reference weights onto the scale.
View Scale Versions	10 Press the T3 button to enter the menu.
G1 Scale HW0.0 FW0.0.0	11 Use T1 and T2 to display the hardware and software version installed.
View Versions Exit	12 Press the T3 button to exit the submenu

Program Scales

Enter Password ****** Scale Settings

- This parameter enables the technician to set some scale parameters like:
 - Enabling/disabling the offset parameter;
 - Setting the weight reading time;
 - Calibrating the scales;
 - Updating the scale software.

Display	Operating Procedure
Scale Exit	13 Press T1 or T2 until the display shows the exit menu, press the T3 button to return to the "Technical" programming.
	14 Press T1 or T2 to continue with the programming of the other parameters.
94.4 00:00 95.5 95.1 SB	Alternatively, you can exit the "Technical" programming and return to the normal use of the espresso machine by pressing T2 and T3 at the same time.

Solenoid Test

Description

Enter Password

Solenoid Test Settings This parameter allows the technician to verify the proper work of all solenoid valves.

Display	Operating Procedure
Enter Password ******	1 After accessing the "Technical" programming menu and entering the password, use the buttons T1 and T2 until the following screen is displayed.
Solenoid Test Settings	2 Press the T3 button to enter the menu.
Test Group G1 Solenoid Testins Solenoid	3 Press the T3 button to start verifying the proper work of coffee group solenoid valve.
Power:12.00W Opened: YES Peak: 9.20W Trough: 7.50W	4 These values indicate the proper work of coffee group solenoid valve.

Solenoid Test

Description

Enter Password

Solenoid Test Settinss This parameter allows the technician to verify the proper work of all solenoid valves.

Display	Operating Procedure
Test Hot Water Solenoid Testins Solenoid	4 Press the T3 button to start verifying the proper work of hot water solenoid valve.
Power:12.00W Opened: YES Peak: 9.20W Trough: 7.50W	5 These values indicate the proper work of coffee group solenoid valve.
Test Autofill Solenoid Testins Solenoid	6 Press the T3 button to start verifying the proper work of autofill solenoid valve.
Power:12.00W Opened: YES Peak: 9.20W Trough: 7.50W	7 These values indicate the proper work of coffee group solenoid valve.

Solenoid Test

Description

Enter Password

Solenoid Test Settings This parameter allows the technician to verify the proper work of all solenoid valves.

Display	Operating Procedure
Solenoid Test Exit	8 Press T1 or T2 until the display shows the exit menu, press the T3 button to return to the "Technical" programming.
	9 Press T1 or T2 to continue with the programming of the other parameters.
94.4 00:80 95.5 95.1 SB	Alternatively, you can exit the "Technical" programming and return to the normal use of the espresso machine by pressing T2 and T3 at the same time.

Coffee Boiler

Enter Password ****** Coffee Boiler Settings

Description

- This parameter enables the technician to set various parameters of the coffee boiler.
- The temperature of the boiler is measured at the most critical point in the boiler where temperature fluctuation is the greatest.
- The temperature of the water exiting the group head is held constant by means of the mass of the group casting. Even

though the temperature of the boiler may vary slightly, the temperature of the water exiting the group is constant.

• To properly calibrate the temperature of any espresso machine it is import to measure the temperature of the water exiting the group by means of an external temperature measuring device. The difference of the display temperature and the measured temperature may be compensated by use of the "Coffee T. Offset" parameter.

Γ	Display		Operating Procedure
[Enter Password ******	1	After accessing the "Technical" programming menu and entering the password, use the buttons T1 and T2 until the following screen is displayed.
	Coffee Boiler Settings	2	Press the T3 button to enter the menu.
[Coffee Boiler 1 ENABLED	3	Press the T3 button to enter the menu, move between the parameters using the buttons T1 and T2 to select ENABLED or DISABLED, press the T3 button to confirm the option.
	CB1 Temperature 93,1°C 93,3°C	4	Press the T3 button to enter the menu, move with the buttons T1 and T2 to set the desired temperature, press the T3 button to confirm the value. In the case of espresso machine with multiple boilers you can set the temperature also on the coffee boiler. The temperature indicated on the left is the actual temperature of the group while the temperature on the right is the set temperature.

Coffee Boiler

Enter Password ****** Coffee Boiler Settings

- The OFFSET parameter is used to calibrate the coffee boiler temperature system to ensure the display temperature accurately represents the temperature of the water exiting the group head.
- This parameter is preset at the factory based upon initial tests of this espresso machine.
- It is not recommended that this number is changed. Changes to this parameter

- can cause unexpected results.
- It is important to write down this value before making changes to be sure you can return to the factory programming if unexpected results occur. Each machine may have a different value as it is set individually.

Display	Operating Procedure	
CB1 Offset 3.0°C	Press the T3 button to enter the menu, move with the buttons T1 and T2 to set the desired temperature, press the T3 button to confirm the value. In the case of espresso machine with 4 groups you can set this value also on the coffee boiler 2.	
Coffee Boiler Exit	6 Press the T3 button to return to the "Technical" programming.	
	7 Press T1 or T2 to continue with the programming of the other parameters.	
Menu Press B3 to Exit	8 To exit the menu move between the parameters using the buttons T1 and T2 until the exit menu is displayed Press the T3 button to exit the menu and return to the normal use of the espresso machine.	

Coffee Boiler

Enter Password ****** Coffee Boiler Settings

Description

- The OFFSET parameter is used to calibrate the coffee boiler temperature system to ensure the display temperature accurately represents the temperature of the water exiting the group head.
- This parameter is preset at the factory based upon initial tests of this espresso machine.
- It is not recommended that this number is changed. Changes to this parameter

- can cause unexpected results.
- It is important to write down this value before making changes to be sure you can return to the factory programming if unexpected results occur. Each machine may have a different value as it is set individually.

Display Operating Procedure 94.4 08:88 95.5 95.1 58 9 Alternatively, you can exit the "Technical" programming and return to the normal use of the espresso machine by pressing T2 and T3 at the same time. WARNING THE COFFEE BOILER CONTAINS WATER AT ELEVATED TEMPERATURES. WATER TEMPERATURE OVER 52°C CAN CAUSE SEVERE BURNS INSTANTIX OR DEATH FROM SCALDING.

Steam Boiler

Enter Password ***** Steam Boiler Settings

- This parameter enables the technician to set various parameters of the steam boiler.
- The temperature of saturated water is proportional to the pressure inside the Steam Boiler. Therefore it is possible to regulate the pressure of the steam boiler by means of electronic temperature control. Please use the following tables as reference when setting the steam boiler temperature.

Temperature	Pressure
247°F/119°C	1.0 bar
260°F/127°C	1.5 bar
264°F/129°C	2.0 bar

Display	Operating Procedure
Enter Password ******	1 After accessing the "Technical" programming menu and entering the password, use the buttons T1 and T2 until the following screen is displayed.
Steam Boiler Settings	2 Press the T3 button to enter the menu.
Steam Boiler ENABLED	Press the T3 button to enter the menu, move between the parameters using the buttons T1 and T2 to select ENABLED or DISABLED, press the T3 button to confirm the option.
Steam Temp. 123,7°C 123,5°C	4 Press the T3 button to enter the menu, move with the buttons T1 and T2 to set the desired temperature, press the T3 button to confirm the value.

Steam Boiler

Enter Password ***** Steam Boiler Settings

Description

- The parameter filling WITH PUMP allows the technician to select the activation of the water pump during the automatic filling cycle of the service boiler.
- Only under unusual circumstances would the option of "WITHOUT PUMP" be chosen.
- The electronics installed in this espresso machine give priority to the brew boiler for pressure. The activation of the auto-fill cycle during the brewing

process can reduce the overall dispensing pressure in the brew boiler.

- During the auto-fill cycle, if a brew cycle is chosen, the auto-fill cycle is delayed until all brew cycles are complete.
- The maximum permitted value for the temperature setting is 129°C.
- SAFETY TEST allows to bring the steam boiler temperature to 140°C, thus triggering the safety valve. Once the

Display	Operating Procedure	
Autofill Delay 2 start 2 stop	The first value indicates the time in seconds between the detection of the need to fill and the start of filling. The second value indicates the time in seconds between filling and its actual end. Press the T3 button to enter the menu, move with the buttons T1 and T2 to set the desired automatic filling time, press the T3 button to confirm the value.	
Fill Durins Brew YES	6 Press the T3 button to enter the menu, move using the buttons T1 and T2 to select YES or NO, press the T3 button to confirm the option.	
Autofill Timeout 10 min	7 Press the T3 button to enter the menu, move with the buttons T1 and T2 to set the desired time, press the T3 button to confirm the value.	
Fill With Pump WITH PUMP	8 Press the T3 button to enter the menu, move between the parameters using the buttons T1 and T2 to select WITH PUMP or WITHOUT PUMP, press the T3 button to confirm the option.	

Enter Password ***** Steam Boiler Settings

Steam Boiler

Description

valve has triggered disable the function.

- Should the safety valve fail to trigger within approximately one minute of the temperature reaching 140°C, disable the function and replace the valve.
- Only qualified technicians can perform this operation.
- DRAIN STEAM BOILER allows the service staff to renew or "regenerate" the water contained inside the steam

boiler, discharging about one half of the water contained in the boiler.

• This procedure is recommended in case the machine should remain inactive for more than 8 hours and in any case at least on a weekly basis.

Display	Operating Procedure
Level Sensitiv.	Press the T3 button to enter the menu, move between the parameters using the buttons T1 and T2 to select HIGH, MEDIUM or LOW, press the T3 button to confirm the option.
Steam Boiler Safety Test	10 Press the T3 button to enable the function.
Safety Test 127.0/140.0°C	11 Press the T3 button to exit the function.
Drain Steam Boiler Close Water Valve Enter when Ready	Press the T3 button to enable the function. Manually close the mixing valve to allow the drain of the water contained in the steam boiler.

Steam Boiler

Description

Enter Password

Steam Boiler

Settings

Display	Operating Procedure
Press Water Button Enter when Empty Wait for Steam Boiler Autofill	Press the hot water button to start draining the water contained in the steam boiler. Press the T3 button when the boiler is empty, wait for refilling completion.
Reset Water Valve Enter when Done	Manually reopen the mixing valve and press the T3 button.
Boiler Completed	Now the procedure to renew or "regenerate" the water inside the steam boiler is completed
Steam Boiler Exit	13 Press the T3 button to return to the "Technical" programming.
	14 Press T1 or T2 to continue with the programming of the other parameters.

Steam Boiler

Description

Enter Password

Steam Boiler

Settings

Display	Operating Procedure
Menu Press B3 to Exit	To exit the menu move between the parameters using the buttons T1 and T2 until the exit menu is displayed. Press the T3 button to exit the menu and return to the normal use of the espresso machine.
94.4 00:00 95.5 95.1 SB	Alternatively, you can exit the "Technical" programming and return to the normal use of the espresso machine by pressing T2 and T3 at the same time.
	A WARNING A
	THE STEAM BOILER CONTAINS WATER AT ELEVATED TEMPERATURES. WATER TEMPERATURE OVER 52°C CAN CAUSE SEVERE BURNS INSTANTLY OR DEATH FROM SCALDING.

Steam Boiler

Enter Password ***** Steam Boiler Settings

- The parameter "Level Sensit." allows the technician to select the probe sensitivity for steam boiler filling according to water hardness.
- The black connection cable corresponds to the working level probe.
- The red connection cable corresponds to the minimum level probe.
- The sensitivity default value is high.

Display	Operating Procedure
Enter Password ******	1 After accessing the "Technical" programming menu and entering the password, use the buttons T1 and T2 until the following screen is displayed.
Steam Boiler Settings	2 Press the T3 button to enter the menu.
Level Sensitiv. HIGH	Press the T3 button to enter the menu, move between the parameters using the buttons T1 and T2 to select HIGH, MEDIUM or LOW, press the T3 button to confirm the option.
Steam Boiler Exit	To exit the submenu move between the parameters using the buttons T1 and T2 until the exit submenu is displayed. Press the T3 button to exit the submenu.

Enter Password ****** Steam Boiler Settings

- The parameter "Level Sensit." allows the technician to select the probe sensitivity for steam boiler filling according to water hardness.
- The black connection cable corresponds to the working level probe.
- The red connection cable corresponds to the minimum level probe.
- The sensitivity default value is high.

Display	Operating Procedure
Menu Press B3 to Exit Restart Machine for Changes	To exit the menu move between the parameters using the buttons T1 and T2 until the exit menu is displayed. Press the T3 button to exit the menu.
	6 Turn the Main Switch to the O position.
94.4 00:00 95.5 95.1 SB	Now it is possible to turn on again the espresso machine; set the main switch to position 1 and press any button to complete machine switch on.
110	

Pre-Infusion or Pre-Brewing

Enter Password ***** Preinfusion Settings

Description

- This parameter allows the operator to program the time of pre-brewing of water with the coffee. Each group can have a different programming.
- Pre-brewing has only two values to be adjusted for each group. The time (in seconds) for which the brewing valve is open during the pre-brewing cycle and the time (in seconds) for which the brewing valve is closed during the

pre-brewing cycle; during this time the pump is active. Once the pre-brewing cycle is over, the normal brewing cycle will continue until the end.

• For an espresso machine composed of three groups, they are identified as Group 1, Group 2 and Group 3.

Display	Operating Procedure
Enter Password ******	1 After accessing the "Technical" programming menu and entering the password, use the buttons T1 and T2 until the following screen is displayed.
Preinfusion Settings	2 Press the T3 button to enter the menu.
Group 1 Pre-Inf 0s Wet Group 1 Pre-Inf 0s Hold	Press T1 or T2 to select the group whose parameters you want to set. 3 By pressing the T3 button the first value will blink. Use the buttons T1 and T2 to reach the value that you want to set, press T3 button to confirm. Repeat this operation to set the second value.
Preinfusion Exit	To exit the submenu move between the parameters using the buttons T1 and T2 until the exit submenu is displayed. Press the T3 button to exit the submenu.

Pre-Infusion or Pre-Brewing

Enter Password ****** Preinfusion Settings

- This parameter allows the operator to program the time of pre-brewing of water with the coffee. Each group can have a different programming.
- Pre-brewing has only two values to be adjusted for each group. The time (in seconds) for which the brewing valve is open during the pre-brewing cycle and the time (in seconds) for which the brewing valve is closed during the
- pre-brewing cycle; during this time the pump is active. Once the pre-brewing cycle is over, the normal brewing cycle will continue until the end
- For an espresso machine composed of three groups, they are identified as Group 1, Group 2 and Group 3.

Display	Operating Procedure
	5 Press T1 or T2 to continue with the programming of the other parameters.
Menu Press B3 to Exit	To exit the menu move between the parameters using the buttons T1 and T2 until the exit menu is displayed. Press the T3 button to exit the menu and return to the normal use of the espresso machine.
94.4 00:00 95.5 95.1 SB	Alternatively, you can exit the "Technical" programming and return to the normal use of the espresso machine by pressing T2 and T3 at the same time.

Cup Warmer

Enter Password ****** Cup Warmer Settings

- This parameter allows the technician to enable or disable the cups heating function.
- This parameter allows the technician to adjust the operating time of the resistance for the heating of the cups.
- This parameter allows the technician to select the operating of the cup warmer by time or by button on the control panel.
- This function is displayed only on the models of espresso machine equipped with this accessory.

Display		Operating Procedure
Enter Password ******	1	After accessing the "Technical" programming menu and entering the password, use the buttons T1 and T2 until the following screen is displayed.
Cup Warmer Settings	2	Press the T3 button to enter the menu.
Cup Warmer TIME	3	Press the T3 button to enter the menu, move between the parameters using the buttons T1 and T2 to select TIME or BY BUTTON, press the T3 button to confirm the option.
Cup Warmer T On 2min Cup Warmer T Off 8min	4	Press the T3 button to enter the menu, move between the parameters with the buttons T1 and T2 to set the desired time, press the T3 button to confirm the value.

Enter Password ****** Cup Warmer Settings

- This parameter allows the technician to enable or disable the cups heating function.
- This parameter allows the technician to adjust the operating time of the resistance for the heating of the cups.
- This parameter allows the technician to select the operating of the cup warmer by time or by button on the control panel.
- This function is displayed only on the models of espresso machine equipped with this accessory.

Display	Operating Procedure
Cup Warmer Exit	To exit the submenu move between the parameters using the buttons T1 and T2 until the exit submenu is displayed. Press the T3 button to exit the submenu.
	6 Press T1 or T2 to continue with the programming of the other parameters.
Menu Press B3 to Exit	7 To exit the menu move between the parameters using the buttons T1 and T2 until the exit menu is displayed. Press the T3 button to exit the menu and return to the normal use of the espresso machine.
94.4 00:00 95.5 95.1 SB	Alternatively, you can exit the "Technical" programming and return to the normal use of the espresso machine by pressing T2 and T3 at the same time.

Auto ON/OFF

Enter Password

Auto On/Off Settings

- This parameter allows the technician to program the espresso machine to turn on at a preset time and turn off at a preset time.
- This feature also allows the espresso machine to remain in the off condition for one repeating closed day.

Display	Operating Procedure	
Enter Password ******		cessing the "Technical" programming menu and entering the password, use the buttons T1 and T2 following screen is displayed.
Auto On/Off Settings	2 Press th	e T3 button to enter the menu.
Auto On/Off ENABLED		e T3 button to enter the menu, move between the parameters using the buttons T1 and T2 to select D or DISABLED, press the T3 button to confirm the option.
Auto On Time 00:00		arameter is enabled, press the T3 button to enter the menu, move with the buttons T1 and T2 to set red time, press the T3 button to confirm the value.

Auto ON/OFF

Description

Enter Password

Auto On/Off

Settings

- This parameter allows the technician to program the espresso machine to turn on at a preset time and turn off at a preset time.
- This feature also allows the espresso machine to remain in the off condition for one repeating closed day.

Display		Operating Procedure
Auto Off Time	5	Press the T3 button to enter the menu, move with the buttons T1 and T2 to set the desired time, press the T3 button to confirm the value.
Closed On NEVER	6	Press the T3 button to enter the menu, move with the buttons T1 and T2 to select an option, press the T3 button to confirm the option.
Auto On/Off Exit	7	To exit the submenu move between the parameters using the buttons T1 and T2 until the exit submenu is displayed. Press the T3 button to exit the submenu.
	8	Press T1 or T2 to continue with the programming of the other parameters.

Auto ON/OFF

Enter Password ****** Auto On/Off Settings

- This parameter allows the technician to program the espresso machine to turn on at a preset time and turn off at a preset time.
- This feature also allows the espresso machine to remain in the off condition for one repeating closed day.

Display	Operating Procedure	
Menu Press B3 to Exit	To exit the menu move between the parameters using the buttons T1 and T2 until the exit menu is displayed. Press the T3 button to exit the menu and return to the normal use of the espresso machine.	
94.4 00:00 95.5 95.1 SB	10 Alternatively, you can exit the "Technical" programming and return to the normal use of the espresso machine by pressing T2 and T3 at the same time.	

Enter Password ****** Clock Time 00:00 SUNDAY

Clock Adjust

- This parameter allows the user to set the time of day and the day of the week.
- This parameter is used to display time and is also used by the "Auto On/Off" parameter
- There are 4 changeable values within this parameter:
 - Hour;
 - Minute;
 - Day of week;
 - Hour Format 12h or 24h.

Display	Operating Procedure
Enter Password ******	1 After accessing the "Technical" programming menu and entering the password, use the buttons T1 and T2 until the following screen is displayed.
Clock Time 00:00 SUNDAY	2 Pressing the T3 button the first value will blink. Use the buttons T1 and T2 to set the clock. Repeat the operation to set the day of the week.
	3 Press T1 or T2 to continue with the programming of the other parameters.
Menu Press B3 to Exit	To exit the menu move between the parameters using the buttons T1 and T2 until the exit menu is displayed. Press the T3 button to exit the menu and return to the normal use of the espresso machine.

Clock Adjust

Enter Password ****** Clock Time 00:00 SUNDAY

- This parameter allows the user to set the time of day and the day of the week.
- This parameter is used to display time and is also used by the "Auto On/Off" parameter
- There are 4 changeable values within this parameter:
 - Hour;
 - Minute;
 - Day of week;
 - Hour Format 12h or 24h.

Display	Operating Procedure
94.4 00:00 95.5 95.1 SB	Alternatively, you can exit the "Technical" programming and return to the normal use of the espresso machine by pressing T2 and T3 at the same time.

ECO Mode

Description

Enter Password

Eco Mode

Settinas

- This parameter allows the technician to set up a temperature to be maintained in case of a temporary non utilization of the espresso machine.
- It is possible to set this parameter also during the normal operation of the machine by pressing T1 and T2 at the same time.

Display	Operating Procedure	
Enter Password ******	After accessing the "Technical" programming menu and entering the password, use the buttons T1 and T2 until the following screen is displayed.	
Eco Mode Settings	2 Press the T3 button to enter the menu.	
Eco Mode Temp -10,0°C	3 Press the T3 button to enter the menu, move between the parameters with the buttons T1 and T2 to set the desired temperature, press the T3 button to confirm the value.	
Auto Eco Time 30	Press the T3 button to enter the menu, move between the parameters with the buttons T1 and T2 to set the desired time (in minutes), press the T3 button to confirm the value. A value of "0" (zero) disables the Eco Mode parameter.	

ECO Mode

Enter Password

Eco Mode Settinas

• This parameter allows the technician to set up a temperature to be maintained in case of a temporary non utilization of the espresso machine.

Description

• It is possible to set this parameter also during the normal operation of the machine by pressing T1 and T2 at the same time.

Display	Operating Procedure		
Eco Mode Exit	5 To exit the submenu move between the parameters using the buttons T1 and T2 until the exit submenu is displayed. Press the T3 button to exit the submenu.		
Menu Press B3 to Exit	6 To exit the menu move between the parameters using the buttons T1 and T2 until the exit menu is displayed. Press the T3 button to exit the menu and return to the normal use of the espresso machine.		
94.4 00:00 95.5 95.1 SB	7 Alternatively, you can exit the "Technical" programming and return to the normal use of the espresso machine by pressing T2 and T3 at the same time.		

Filter Alarm Enter Password ****** Filter Alarm Settings

- This parameter enables the technician to program an alarm that will alert the user about the need for maintenance or replacement of the water filter.
- Once the set volume has been reached, the error message "Filter Alarm" will be displayed.
- A value of 0 (zero) disables the filter alarm parameter.
- This feature can be enabled or disabled.

Display	Operating Procedure
Enter Password ******	1 After accessing the "Technical" programming menu and entering the password, use the buttons T1 and T2 until the following screen is displayed.
Filter Alarm Settings	2 Press the T3 button to enter the menu.
Filter Alarm ENABLED	Press the T3 button to enter the menu, move between the parameters using the buttons T1 and T2 to select ENABLED or DISABLED, press the T3 button to confirm the option.
Filter Status 0 of 5000L	4 Press the T3 button to enter the menu, move between the parameters with the buttons T1 and T2 to set the desired value, press the T3 button to confirm the value.

Filter Alarm

Enter Password ****** Filter Alarm

Settinas

- This parameter enables the technician to program an alarm that will alert the user about the need for maintenance or replacement of the water filter.
- Once the set volume has been reached, the error message "Filter Alarm" will be displayed.
- A value of 0 (zero) disables the filter alarm parameter.
- This feature can be enabled or disabled.

Display	Operating Procedure		
Alarm Water Use 40 Coffee Water	Press the T3 button to enter the menu, move between the parameters with the buttons T1 and T2 to set the desired value, press the T3 button to confirm the value.		
Filter Alarm Reset (0 L)	6 Press the T3 button to enter the menu, move between the parameters with the buttons T1 and T2 to set the desired value, press the T3 button to confirm the value.		
Filter Alarm Exit	7 To exit the submenu move between the parameters using the buttons T1 and T2 until the exit submenu is displayed. Press the T3 button to exit the submenu.		
	8 Press T1 or T2 to continue with the programming of the other parameters.		

Enter Password ***** Filter Alarm Settings

Filter Alarm

- This parameter enables the technician to program an alarm that will alert the user about the need for maintenance or replacement of the water filter.
- Once the set volume has been reached, the error message "Filter Alarm" will be displayed.
- A value of 0 (zero) disables the filter alarm parameter.
- This feature can be enabled or disabled.

Display		Operating Procedure
Menu Press B3 to Exit	9	To exit the menu move between the parameters using the buttons T1 and T2 until the exit menu is displayed. Press the T3 button to exit the menu and return to the normal use of the espresso machine.
94.4 00:00 95.5 95.1 SB	10	Alternatively, you can exit the "Technical" programming and return to the normal use of the espresso machine by pressing T2 and T3 at the same time.

Coffee Dose Counter

Description

Enter Password

Coffee Dose

Settings

- This parameter allows the technician to review the total doses dispensed for each button.
- This parameter displays different values:
 - Total coffee doses;
 - Coffee doses for each button:
 - Hot water doses.

Display	Operating Procedure
Enter Password ******	After accessing the "Technical" programming menu and entering the password, use the buttons T1 and T2 until the following screen is displayed.
Coffee Dose Settings	2 Press the T3 button to enter the menu.
Total Coffee Doses: 63	3 Move between the parameters using the buttons T1 and T2 to display the desired option.
G1 Doses 10	4 Continuing to move with the buttons T1 and T2 you can display the total doses of each button.

Coffee Dose Counter

Enter Password ****** Coffee Dose Settings

- This parameter allows the technician to review the total doses dispensed for each button.
- This parameter displays different values:
 - Total coffee doses;
 - Coffee doses for each button:
 - Hot water doses.

Display	Operating Procedure
Water Doses 30	5 Continuing to move with the buttons T1 and T2 you can also display the total doses of the hot water button.
Coffee Dose Exit	6 To exit the submenu move between the parameters using the buttons T1 and T2 until the exit submenu is displayed. Press the T3 button to exit the submenu.
	7 Press T1 or T2 to continue with the programming of the other parameters.
Menu Press B3 to Exit	To exit the menu move between the parameters using the buttons T1 and T2 until the exit menu is displayed. Press the T3 button to exit the menu and return to the normal use of the espresso machine.

Coffee Dose Counter

Enter Password ****** Coffee Dose Settings

- This parameter allows the technician to review the total doses dispensed for each button.
- This parameter displays different values:
 - Total coffee doses;
 - Coffee doses for each button;
 - Hot water doses.

Display	Operating Procedure
94.4 00:00 95.5 95.1 SB	Alternatively, you can exit the "Technical" programming and return to the normal use of the espresso machine by pressing T2 and T3 at the same time.

Electronics

Description

Enter Password

Electronics

Settings

• This parameter allows the technician to display the hardware and firmware version for all the electronic boards installed on the espresso machine.

Display	Operating Procedure
Enter Password ******	1 After accessing the "Technical" programming menu and entering the password, use the buttons T1 and T2 until the following screen is displayed.
Electronics Settings	2 Press the T3 button to enter the menu.
Force FW Upgrade ENABLED	3 Press the T3 button to enter the menu, move between the parameters using the buttons T1 and T2 to select ENABLED or DISABLED, press the T3 button to confirm the option.
Button Board H⊎3	4 Using the buttons T1 and T2 to display the hardware and firmware version for the Button Board.

Electronics

Description

Enter Password

Electronics

Settings

• This parameter allows the technician to display the hardware and firmware version for all the electronic boards installed on the espresso machine.

Display	Operating Procedure
24V Universal HW0 FW0.6.0	5 Using the buttons T1 and T2 to display the hardware and firmware version for the Universal Board.
G1 Scale HW3.0 FW2.7.3	6 Using the buttons T1 and T2 to display the hardware and firmware version for the Scale.
BLE Chip FW0.1.0	7 Using the buttons T1 and T2 to display the hardware and firmware version for the Bluetooth. (if present)
Electronics Exit	8 To exit the submenu move between the parameters using the buttons T1 and T2 until the exit submenu is displayed. Press the T3 button to exit the submenu.

Electronics

Description

Enter Password

Electronics

Settings

• This parameter allows the technician to display the hardware and firmware version for all the electronic boards installed on the espresso machine.

Display		Operating Procedure
	9	Press T1 or T2 to continue with the programming of the other parameters.
Menu Press B3 to Exit	10	To exit the menu move between the parameters using the buttons T1 and T2 until the exit menu is displayed. Press the T3 button to exit the menu and return to the normal use of the espresso machine.
94.4 00:00 95.5 95.1 SB	11	Alternatively, you can exit the "Technical" programming and return to the normal use of the espresso machine by pressing T2 and T3 at the same time.

Barista Lights

Description

Enter Password

Barista Lights

Settings

- This parameter allows the technician to adjust the brightness of the barista lights.
- This parameter allows the operator to set up the brightness to be maintained in case of a temporary non utilization of the espresso machine.

Display	Operating Procedure
Enter Password *****	1 After accessing the "Technical" programming menu and entering the password, use the buttons T1 and T2 until the following screen is displayed.
Barista Lights Settings	2 Press the T3 button to enter the menu.
Not Brewins 40,0%	3 Press the T3 button to enter the menu, move with the buttons T1 and T2 to set the desired value, press the T3 button to confirm the value.
Brewins 100,0 %	4 Press the T3 button to enter the menu, move with the buttons T1 and T2 to set the desired value, press the T3 button to confirm the value.

Barista Lights

Enter Password

Barista Lights Settings

- This parameter allows the technician to adjust the brightness of the barista lights.
- This parameter allows the operator to set up the brightness to be maintained in case of a temporary non utilization of the espresso machine.

Display	Operating Procedure
Eco Mode 5 %	5 Press the T3 button to enter the menu, move with the buttons T1 and T2 to set the desired value, press the T3 button to confirm the value.
Barista Lights Exit	6 To exit the submenu move between the parameters using the buttons T1 and T2 until the exit submenu is displayed. Press the T3 button to exit the submenu.
94.4 00:00 95.5 95.1 SB	7 Press T2 and T3 at the same time to exit the programming mode and return to the normal use of the espresso machine.

Water Quality

Description

Enter Password

H20 Conductivity DISABLED • This parameter allows the technician to evaluate water quality.

Display	Operating Procedure
Enter Password ******	1 After accessing the "Technical" programming menu and entering the password, use the buttons T1 and T2 until the following screen is displayed.
H20 Conductivity DISABLED	Press the T3 button to enter the menu, move between the parameters using the buttons T1 and T2 to select ENABLED or DISABLED, press the T3 button to confirm the option.
Menu Press B3 to Exit	To exit the menu move between the parameters using the buttons T1 and T2 until the exit menu is displayed. Press the T3 button to exit the menu and return to the normal use of the espresso machine.
94.4 00:00 95.5 95.1 SB	4 Alternatively, you can exit the "Technical" programming and return to the normal use of the espresso machine by pressing T2 and T3 at the same time.

Save and Load USB

Description

Enter Password

Save and Load USB Settings

Display	Operating Procedure
Enter Password ******	1 After accessing the "Technical" programming menu and entering the password, use the buttons T1 and T2 until the following screen is displayed.
Save and Load USB Settings	2 Press the T3 button to enter the menu.
Load Settinas From USB	3 Press the T3 button to enter the menu.
Insert USB Key Enter to Exit Loading Settings	4 Insert the USB Pendrive into the USB port and press the T3 button.

Save and Load USB

Description

Enter Password

Save and Load USB Settings

Display	Operating Procedure
Settines Successfully Loaded	5 Confirmation message: all settings have been successfully loaded.
Save Barista Settings to USB	6 Press the T3 button to enter the menu.
Insert USB Key Enter to Exit Saving Settings	7 Insert the USB Pendrive into the USB port and press the T3 button.
Settings Successfully Saved	8 Confirmation message: all settings have been successfully saved.

Save and Load USB

Description

Enter Password

Save and Load USB Settings

Display	Operating Procedure
Save Technician Settings to USB	9 Press the T3 button to enter the menu.
Insert USB Key Enter to Exit Savins Settinss	10 Insert the USB Pendrive into the USB port and press the T3 button.
Settings Successfully Saved	11 Confirmation message: all settings have been successfully saved
Electronics Exit	To exit the submenu move between the parameters using the buttons T1 and T2 until the exit submenu is displayed. Press the T3 button to exit the submenu.

Save and Load USB

Description

Enter Password

Save and Load USB Settings

Display	Operating Procedure				
	13 Press T1 or T2 to continue with the programming of the other parameters.				
Menu Press B3 to Exit	To exit the menu move between the parameters using the buttons T1 and T2 until the exit menu is displayed. Press the T3 button to exit the menu and return to the normal use of the espresso machine.				
94.4 00:00 95.5 95.1 SB	15 Alternatively, you can exit the "Technical" programming and return to the normal use of the espresso machine by pressing T2 and T3 at the same time.				

Reset Enter Password ****** Reset Settings

- This parameter allows the technician to reset all the values returning to initial factory settings.
- It is possible to reset the settings you made in the "Barista" programming or the settings you made in the "Technical" programming.

Display	Operating Procedure				
Enter Password ******	1 After accessing the "Technical" programming menu and entering the password, use the buttons T1 and T2 until the following screen is displayed.				
Reset Settings	2 Press the T3 button to enter the menu.				
Barista Settings Reset	3 Press the T3 button to reset the settings you made in the "Barista" programming.				
Tech, Settings Reset	4 Press the T3 button to reset the settings you made in the "Technical" programming.				

Reset Enter Password ****** Reset Settings

- This parameter allows the technician to reset all the values returning to initial factory settings.
- It is possible to reset the settings you made in the "Barista" programming or the settings you made in the "Technical" programming.

Display		Operating Procedure						
Reset Exit	5	To exit the submenu move between the parameters using the buttons T1 and T2 until the exit submenu displayed. Press the T3 button to exit the submenu.						
	6	Press T1 or T2 to continue with the programming of the other parameters.						
Menu Press B3 to Exit	7	To exit the menu move between the parameters using the buttons T1 and T2 until the exit menu is displayed. Press the T3 button to exit the menu and return to the normal use of the espresso machine.						
94.4 00:00 95.5 95.1 SB	8	Alternatively, you can exit the "Technical" programming and return to the normal use of the espresso machin by pressing T2 and T3 at the same time.						

First Startup

Description

• This parameter allows the technician to enable/disable first startup procedure.

Enter Password

First Startup

ENABLED

Display	Operating Procedure				
Enter Password ******	1 After accessing the "Technical" programming menu and entering the password, use the buttons T1 and T2 until the following screen is displayed.				
First Startup ENABLED	Press the T3 button to enter the menu, move between the parameters using the buttons T1 and T2 to select ENABLED or DISABLED, press the T3 button to confirm the option.				
Menu Press B3 to Exit	To exit the menu move between the parameters using the buttons T1 and T2 until the exit menu is displayed. Press the T3 button to exit the menu and return to the normal use of the espresso machine.				
94.4 00:00 95.5 95.1 SB	4 Alternatively, you can exit the "Technical" programming and return to the normal use of the espresso machine by pressing T2 and T3 at the same time.				

Update Firmware

Description

Enter Password

Update Firmware

• This parameter allows the technician to update the control unit of the espresso machine via a USB Pendrive.

Display	Operating Procedure				
Enter Password *****	1 After accessing the "Technical" programming menu and entering the password, use the buttons T1 and T2 until the following screen is displayed.				
Update Firmware	2 Press the T3 button to update the firmware. The following screen will immediately appear.				
Insert USB Key And Press Enter	3 Insert the USB Pendrive into the USB port and press the T3 button.				
OFF 00:00	4 When the update is over, the espresso machine restarts. Set the switch to 0 (zero) and then again to 1.				

Enter Password ******* Menu

Press B3 to Exit

Description

• This parameter allows the technician to exit the "Technical" programming and return to the normal use of the espresso machine.

Display	Operating Procedure			
Menu Press B3 to Exit	1 Press the T3 button 6 to exit the "Technical" programming and return to the normal use of the espresso machine.			