

la marzocco
kb90



KB90
**the ultimate workflow
machine featuring the
straight-in portafilter**

AVAILABLE CONFIGURATIONS



no. groups: **2 | 3**

configurations: **AV | ABR**

The KB90 is the ultimate evolution of the Linea PB form, designed to optimize workflow for baristas by improving the ergonomics and features of the machine. The Straight-In Portafilter removes strain on baristas that causes repetitive stress injuries.

Efficiency is also increased thanks to Steam Flush: after each extraction, a burst of steam purges the brew path and is followed by a flush of hot water, keeping the group heads clean even during the busiest hours.

KB90 HIGHLIGHT

straight-in portafilter

Designed to simplify the motions required to engage the portafilter and reduce strain by 12x on the barista for even greater performance and everyday usability. High-volume coffee environments demand that a barista can work quickly and efficiently to produce drinks during the busiest periods of the day. The Straight-In Portafilter can noticeably mitigate repetitive stress injuries through its ease of action improving the natural workflow and output of the barista.

FEATURES

independent brew boilers

Separate boilers for each group head allow baristas to optimize temperature for individual coffees

steam flush

Keeps the groups clean with an automatic burst of steam and a flush of hot water between extractions

auto brew ratio / drip prediction

Precision scales incorporated into the drip tray improve beverage consistency by stopping extraction based on mass, while Drip Prediction uses an algorithm to improve shot accuracy

easy rebuild steam valve

Engineered so the valve can be serviced directly from the front of the machine without needing to be removed

pro touch steam wands

Vacuum-insulated double-walled steam wands remain cool while delivering high-volume dry steam

SPECIFICATIONS

| | 2 group | 3 group |
|---------------------------------------|--|---------------------|
| dimensions (W x D x H) | 32" x 24.5" x 21" | 41.5" x 24.5" x 21" |
| weight (lbs) | 170 | 223 |
| voltage (VAC, phase, Hz) | 208-240, 1, 60 | 208-240, 1, 60 |
| element wattage | 5400, 5700 | 7300, 7800 |
| steam boiler capacity (liters) | 7 | 11 |
| brew boiler capacity (liters) | 1.3 x2 | 1.3 x3 |
| amp service required | 30 | 50 |
| certifications | UL-197, NSF-8, CAN / CSA-C22.2 No. 109 | |

SALES INQUIRIES 206-706-9104 (Option 3) info.usa@lamarzocco.com www.lamarzoccousa.com