



# la marzocco

1553 NW Ballard Way, Seattle, WA 98107

La Marzocco  
Mazzer

Phone: 206.706.9104 (x101 Tech.)  
Avail.: 6:00 a.m.–5:30 p.m. M–F  
Fax: 206.706.9106  
Web: www.lamarzoccousa.com

## Preventative Maintenance Checklist Linea Classic 12 Month

Please fill out all sections completely

Customer Name: _____	Phone: _____
Location Address: _____	
Machine Model: _____	Serial Number: _____

### All Models

- Test Water, Pre and Post Filtration, with La Marzocco Water Test Kit (F.9.0000) and Complete Form Below
  - Clean and Backflush Machine
  - Replace Group Gaskets
  - Replace Diffuser Screens (F.3.040)
  - Inspect Drain System
  - Rebuild Steam Valves (L165/K)
  - Inspect Steam Boiler Pressure-Stat (L270)
  - Clean Auto-Fill Probe And Test Operation
  - Inspect Steam Boiler Contactor (L500 or L510)
  - Test Flow Rate (milliliters in 30 seconds)
  - Test Brew Temperature
  - Test Brew Pressure
  - Test All Switches for Proper Operation
  - Inspect Portafilter Baskets
- 8 mm (H.3.001)
  - 9 mm (H.3.002)
  - Replace Steam Valve Anti-Suction Valve (L192)
  - Replace Steam Boiler Vacuum Breaker (L190)
  - Replace Pressure Safety Valve (B.2.024)
  - Acceptable     Replaced
  - Operational     Replaced Parts: \_\_\_\_\_
  - Acceptable     Replaced With Part Number: \_\_\_\_\_
  - Group 1: \_\_\_\_\_ Group 2: \_\_\_\_\_ Group 3: \_\_\_\_\_ Group 4: \_\_\_\_\_
  - Set Value: \_\_\_\_\_ Actual: \_\_\_\_\_
  - Set Value: \_\_\_\_\_ Actual: \_\_\_\_\_
  - Operational     Replaced Parts: \_\_\_\_\_
  - Acceptable     Replaced With Part Number: \_\_\_\_\_

### If AV Model

- Test Shot Volumes
- Test DC Voltage \_\_\_\_\_ VDC
- Test Flow Meter Resistance (2.2 kΩ ±10%)    Group 1: \_\_\_\_\_ Group 2: \_\_\_\_\_ Group 3: \_\_\_\_\_ Group 4: \_\_\_\_\_

### If MP Model

- Rebuild MP valve with SA600/K2.

La Marzocco Water Specifications				Your Test Results	
Value	Units	Minimum	Maximum	Pre Filtration	Post Filtration
Total Dissolved Solids (TDS)	ppm	90	150		
Total Hardness	ppm	70	100		
Total Iron	ppm	0	0.02		
Free Chlorine	ppm	0	0.05		
Total Chlorine	ppm	0	0.1		
pH		6.5	8		
Alkalinity	ppm	40	80		
Chloride	ppm	0	30		
Pressure: 45–80 psi (3–5.5 bar)		Flow Rate: 2 gal./min. (≈ 8 l/min.)		1 gpg US = 17.1 ppm = 17.1 mg/l	
Brand & Model of Water Filtration System: _____					

Service Company: \_\_\_\_\_

Technician: \_\_\_\_\_ Technician Signature: \_\_\_\_\_

Customer Signature: \_\_\_\_\_ Name (Please Print): \_\_\_\_\_