

la marzocco



gb5 s



GB5 S

**elegant design married
with proven reliability**

AVAILABLE CONFIGURATIONS

//////

no. groups: **2 | 3 | 4**

configurations: **EE | AV | ABR**

Equipped with proprietary La Marzocco electronics and advanced temperature stability, the GB5 S combines classical European design with cutting edge performance. The red lilies on the sides recall our Florentine heritage, while partially exposed groups offer a streamlined barista working experience. The machine provides control over boiler temperature, brewing volume, automatic cleaning cycles, and more to keep high quality coffee flowing even during the busiest hours.

GB5 S HIGHLIGHT



classic italian design

The gracious lines and harmonious curves of the GB5 S speak to the La Marzocco heritage of design and intention. The understated side shields, elegant Florentine lilies, and subtle insignia of il marzocco on the cup rail,



combine to give this machine the feel of an heirloom built to stand the test of time.

FEATURES



piero group caps (AV and ABR)

Re-engineered internal water path that increases temperature stability

dual PIDs (brew and steam)

auto backflush

dimnable barista lights (AV and ABR)

3-stage LED lights for eco, on, and brewing modes allow you to focus on your extraction and the cup

pro app compatible

ruby flow restrictors

easy rebuild steam valve

Engineered so the valve can be serviced from the front of the machine without needing to be removed

pro touch steam wands (optional)

Vacuum-insulated double-walled steam wands remain cool while delivering high-volume dry steam

SPECIFICATIONS

| | 2 group | 3 group | 4 group |
|---------------------------------------|--|----------------------------|--------------------------|
| dimensions (W x D x H) | 29" x 25" x 18.5" *21.4" | 38.5" x 25" x 18.5" *21.4" | 48" x 25" x 18.5" *21.4" |
| weight (lbs) | 150 | 171 | 198 |
| voltage (VAC, phase, Hz) | 208-240, 1, 60 | 208-240, 1, 60 | 208-240, 1, 60 |
| element wattage | 5200 | 6800 | 8300 |
| steam boiler capacity (liters) | 7 | 11 | 15 |
| brew boiler capacity (liters) | 3.4 | 5 | 3.4 x2 |
| amp service required | 30 | 50 | 50 |
| certifications | UL-197, NSF-4, CAN / CSA-C22.2 No. 109 | | |

SALES INQUIRIES 206-706-9104 (Option 3) info.usa@lamarzocco.com www.lamarzoccousa.com