### la marzocco



# kb90



## the ultimate workflow machine featuring the straight-in portafilter

#### AVAILABLE CONFIGURATIONS

no. groups: 2 | 3 configurations: AV | ABR

The KB90 is the ultimate evolution of the Linea PB form, designed to optimize workflow for baristas by improving the ergonomics and features of the machine. The Straight-In Portafilter removes strain on baristas that causes repetitive stress injuries.

Efficiency is also increased thanks to Steam Flush: after each extraction, a burst of steam purges the brew path and is followed by a flush of hot water, keeping the group heads clean even during the busiest hours.

#### **KB90 HIGHLIGHT**

## straight-in portafilter

Designed to simplify the motions required to engage the portafilter and reduce strain by 12x on the barista for even greater performance and everyday usability. Highvolume coffee environments demand that a barista can work quickly and efficiently to produce drinks during the busiest periods of the day. The Straight-In Portafilter can noticeably mitigate repetitive stress injuries through its ease of action improving the natural workflow and output of the barista.

#### **FEATURES**

#### independent brew boilers

Separate boilers for each group head allow baristas to optimize temperature for individual coffees

#### steam flush

Keeps the groups clean with an automatic burst of steam and a flush of hot water between extractions

## auto brew ratio / drip prediction

Precision scales incorporated into the drip tray improve beverage consistency by stopping extraction based on mass, while Drip Prediction uses an algorithm to improve shot accuracy

#### easy rebuild steam valve

Engineered so the valve can be serviced directly from the front of the machine without needing to be removed

#### pro touch steam wands

Vacuum-insulated double-walled steam wands remain cool while delivering high-volume dry steam

SPECIFICATIONS	2 group	3 group
dimensions (W x D x H)	32" x 24. <sup>5</sup> " x 21"	41.5" x 24.5" x 21"
weight (lbs)	170	223
voltage (VAC, phase, Hz)	208-240, 1, 60	208-240, 1, 60
element wattage	5400, 5700	7300, 7800
steam boiler capacity (liters)	7	11
brew boiler capacity (liters)	1.3 x2	1.3 x3
amp service required	30	50
certifications	UL-197, NSF-4, CAN / CSA-C22.2 No. 109	