la marzocco



linea pb



a comprehensive update to the technical and stylistic workings of an industry icon

AVAILABLE CONFIGURATIONS

no. groups: 2 | 3 | 4 configurations: AV | ABR

The Linea PB represents the first full update to the Linea Classic since it was released in 1989. The Linea PB features the iconic La Marzocco polished stainless steel body, updated with refined and sharpened design elements and a lower profile.

To complement its stylistic updates, the Linea PB features improved component longevity and new electronics that give the barista control over functions directly from the machine interface – including boiler temperatures, brewing volume, hot water tap dose, and auto-backflush, among others.

LINEA PB HIGHLIGHT

la marzocco user interface

Proprietary electronics drive intuitive programming and provide heads-up information and systems monitoring on a digital display:

- Shot timers
- Flow pulse counter
- USB firmware updates
- Boiler temperatures
- System alerts
- ECO mode

FEATURES

dual PIDs (brew and steam)

Allows you to electronically control brew and steam boiler temperatures

piero group caps

Re-engineered internal water path that increases temperature stability

auto backflush

Simplifying end-of-shift cleaning processes for baristas ensures that machines are cleaned more often and correctly

clog reducing flow restrictors

A flow restrictor integrated into the solenoid valve reduces scale formation and clogging while ensuring a consistent flow rate.

abr- drip tray sclaes (optional)

Precision scales incorporated into the electronics system provide the barista control over beverage mass

la marzocco SmartSteam (optional)

Integrated probe ensures machine stops steaming at the programmed temperature every time

SPECIFICATIONS	2 group	3 group	4 group
dimensions (W x D x H)	28" x 23.3" x 21"	37.5" x 23.3" x 21"	46.9" x 23.3" x 21"
weight (lbs)	179	205	258
voltage (VAC, phase, Hz)	208-240, 1, 60	208-240, 1, 60	208-240, 1, 60
element wattage	4600	6100	8000
steam boiler capacity (liters)	7	11	14.5
brew boiler capacity (liters)	3.4	5	3.4 x 2
amp service required	30	50	50
certifications	UL-197, NSF-4, CAN / CSA-C22.2 No. 109		