


U.S. installation guideline

linea classic s



Specifications	1 group	2 group	3 group	4 group
Height	20.5"	20.5"	20.5"	20.5"
Width	20"	28"	37"	46"
Depth	23"	23"	23"	23"
Weight	90 lbs	130 lbs	164 lbs	236 lbs
Power				
Voltage/Phase/Cycle	208-240 VAC 1Φ 60Hz			
Wattage	2500	4600	6100	8000
Full Load Amp Draw	12	22	28	37
Max. Dist. from Outlet*	5'	5'	5'	5'
NEMA Plug and Outlet*	6-20P; 6-20R	6-30P; 6-30R	6-50P; 6-50R	6-50P; 6-50R

Water	Drainage	External Pump	
Water Flow Rate	2GPM	Dimensions	12" × 12" × 12"
Dynamic Water Pressure †	45PSI	Max. Dist. from Water Supply*	4'
Min. Pipe Size Diameter*	3/8"	Max. Dist. from Machine	8'
Water Connection*	3/8" male comp.	Counter Hole Diameter	2.5"
Water Quality	Contact us for a free water test kit. See water specifications.		


* suggested | † regulate as needed | ° Height from the base of the machine to the group head

‡ This machine must be installed in accordance with the applicable federal, state and local plumbing codes




la marzocco

handmade in florence



top view

1. center line of the machine
 2. position of the power cord
 3. suggested diameter of counter hole:
2.5"
 4. position of the drain tube
 5. position of the water inlet hose
 6. width of legs per model
- ⊗ machine leg location



front view

1. 3/8" cold water supply
2. water filter required (not provided),
see water specifications below.
- 3a. 3/8" compression cold water supply line
suggested max. dist. from water supply
4'
- 3b. 3/8" BSPP cold water supply line
suggested max. dist. from water supply
8'
4. pump and motor
5. electrical supply to motor from machine
6. 3/4" flexible drainline (min. 0.25"/1'
slope)
7. floor drain
8. 110V, 15amp elec. supply to grinder
9. 208-240V single phase elec. supply to

water specifications

La Marzocco recommends that your filtration system produces water with the following properties:

T.D.S.	90—150ppm
Total Hardness	70—100 ppm
Total Iron	0—0.02ppm
Free Chlorine	0—0.05ppm
Total Chlorine	0—0.1ppm

pH	6.5—8
Alkalinity	40—80ppm
Chloride	0—30ppm
Line Pressure	45—80 PSI
Flow Rate	2 GPM or 8 LPM