

la marzocco



strada x



STRADA X
designed for
and by baristas

AVAILABLE CONFIGURATIONS

///////

no. groups: **1 | 2 | 3**

configurations: **X**

The Strada X is the culmination of La Marzocco's innovative espresso technology. Blending workflow efficiency with groundbreaking pressure profiling, the Strada X gives baristas total control over the shots they pull while maintaining unprecedented repeatability.

Named for the "Street Team" of baristas, technicians, and coffee professionals who helped design the original Strada, the Strada X continues La Marzocco's legacy of coffee-forward, cutting-edge espresso innovation.

STRADA X HIGHLIGHT



three distinct brewing modes

Manual Brewing allows the barista to manually create a pressure profile by moving the paddle between 0 and 12 bars of pressure.

Profile Brewing lets the barista select an existing profile to run automatically when the paddle is engaged.

AV Brewing allows the barista to set a target weight and run espresso with consistent pressure.

FEATURES



mass-based profiling
Integrated scales allow for a new standard in precision and repeatability using beverage mass to control the pressure curve.

smart saturation
The Smart Saturation feature introduced in the Strada X monitors the flow rate of the water to take guesswork out of preinfusion and ensure ultimate consistency.

paddle-based profile control
Use the group head paddle to set pressure inputs that extract espresso just how you want. Strada X then automatically tunes your pressure inputs into a weight-based profile for consistency and precision.

straight-in portafilters (optional)
Designed to simplify the motions required to engage the portafilter and reduce strain by 12x on the barista for even greater performance and everyday usability.

SPECIFICATIONS	1 group	2 group	3 group
dimensions (W x D x H)	20.9" x 27.2" x 19.7"	32.7" x 27.2" x 19.7"	40.6" x 27.2" x 19.7"
weight (lbs)	132.3	207.3	222.7
voltage (VAC, phase, Hz)	208-240, 1, 60	208-240, 1, 60	208-240, 1, 60
element wattage	2037—2220	4800—5666	6730—7783
steam boiler capacity (liters)	3.5	8.2	11.8
brew boiler capacity (liters)	1.3	1.3 x 2	1.3 x 3
amp service required	15	30	50
certifications	UL-197, NSF-4, CAN / CSA-C22.2 No. 109		